

Residential/Commercial Combustion Analyzer Kit w/ Printer C165+KIT



Residential/Commercial Combustion Analyzer Kit w/ Printer





10 YEAR NARRANTY





Functions

- Measures: CO (10,000ppm H2 Compensated), CO2, Differential Pressure, Flue and Inlet Temperature
- Calculates: Differential Temperature, Efficiency (Net, Gross), Excess Air

Features

- Backed by UEi Service+
- Up to 10-Year warranty with annual recertification
- LINK to wireless probes
- Wireless Flow and Return Probes
- NOx filtered & H2 Compensated CO sensor (10,000ppm range)
- Over-range protection pump
- NOx filtered CO sensor
- Low Flow Detection to protect reading accuracy
- Compatible with DTHA2
- Room CO test
- Differential Pressure
- Heat Exchanger test
- Protective water trap
- Wireless connection to a Free Printer App (iOS® and Android™ Compatible)



LINK to wireless Flow and Return pipe clamp probes.





Includes


- Flue Probe (CP2)
- IR Thermal Printer (IRP-2)
- Printer Paper Roll (spare) (16646)
- Rechargeable Batteries 3 (AA)
- USB Charging Cable (WIR0067)
- Wireless Pipe Clamp Probes 2 (WPC2)
- Tubing w/ connector (11000)
- K-Type Thermocouples 2 (ATT29)
- Particle Filter (spare) (17631)
- Carrying Case (AC509)
- Quick Start Guide













Residential/Commercial Combustion Analyzer Kit w/ Printer



C165+KIT

Specifications

TEMPERATURE MEASUREMENT

Parameter	Range	Resolution	Accuracy
Flue temperature	32° to 1112°F	0.1°F	±(0.3% rdg +3.6°F (2°C))
Inlet temperature (internal sensor)	32° to 112°F	0.1°F	+1.8°C +0.3% rdg
Inlet temperature (external sensor)	32° to 1112°F	0.1°F	+3.6°F +0.3% rdg

FLUE GAS

Parameter	Range	Resolution	Accuracy
Oxygen	0 to 21%	0.1%	+0.3% Volume
Carbon Monoxide	0 to 2000ppm	1ppm	±3ppm or ±5% of rdg
	2000 to 9999ppm		±10% of rdg
	Above 9999ppm		Unspecified
Carbon Dioxide	0 to 20%	0.1%	0.3% rdg
Efficiency (Net or Gross)	0 to 99.9%	0.1%	+1.0% rdg
Efficiency High (C)	0 to 119.9%	0.1%	+1.0% rdg
Excess Air	0 to 250%	0.1%	+0.2% rdg
CO/CO2 ratio	0 to 0.999%	0.0001	+5% rdg

PRESSURE (DIFFERENTIAL)

Parameter	Range	Resolution	Accuracy
Pressure (Differential)	±80mbar	0.1mbar	±0.5% FSD

PRE-PROGRAMMED FUELS	Natural Gas, Propane, Butane, LPG, Light Oils (28/35sec), Wood Pellets, Town Gas, Coke Gas, Bio Oil, Bio Gas
----------------------	--

USER PROGRAMMED FUELS	5 User defined fuels

STORAGE CAPACITY	30 tests

Downloads



Manual



Data Sheet



