




CABLE-4-20MA

4 to 20 mA Input

Cable, 18.5 inches in length, for connecting a sensor with a 4-20mA output to a HOBO U12, UX120, MX1100, or ZW series external-channel data logger, to expand the range of measurement options and applications.



Key Advantages:

- 18.5 inches in length
- Can be plugged directly into the external input jacks of U12, UX120, or ZW series loggers to expand the range of measurement options and applications.

HOBO CABLE-4-20MA Specifications

Measurement range: 0 to 20.1 mA

Accuracy with U12: ± 0.02 mA $\pm 2.5\%$ of absolute current

Accuracy with ZW: ± 0.015 mA $\pm 2.0\%$ of absolute current

Accuracy with UX120-006M, MX1104, and MX1105: ± 0.001 mA $\pm 0.2\%$ of absolute current

Resolution with U12 and ZW: 0.03% of full scale

Resolution with UX120-006M, MX1104, and MX1105: 0.002% of full scale

Cable length: 47 cm (18.5 inches)

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

▶ Email sales@onsetcomp.com

▶ Call 1-508-759-9500

▶ In U.S. toll free 1-800-564-4377

▶ Fax 1-508-759-9100

Technical Support (8am to 6pm ET, Monday through Friday)

▶ Contact Product Support www.onsetcomp.com/support/contact

▶ Call 1-508-759-9500

▶ In U.S. toll free 1-877-564-4377

Onset Computer Corporation

470 MacArthur Boulevard

Bourne, MA 02532