



PRODUCT SPECIFICATIONS

75" 6000A+ Series



75" Panel Specifications

Size	75"
Screen Type	4K Ultra HD
Aspect Ratio	16:9
Display Area	64.97" × 36.55"
Resolution	3840(H) × 2160(V)
Pixel Pitch	.42976 mm × .42975 mm
Back Light Unit	Direct type LED
Response Time	8 ms
Refreshing Frequency	60Hz
Display Color	1.07B (10 bit)
Brightness	400 cd/m ²
Contrast Ratio	5000:1
Viewing Angle	178°
Life Time	≥50,000 hours

6000A+ SERIES INTERACTIVE PANELS

The first EDLA Certified Interactive Panel series.



IMPROVED DEVICE MANAGEMENT



2.2 SOUND CHANNEL WITH TOP MOUNTED SPEAKERS



USB-C CABLE (AUDIO, VIDEO, TOUCH, AND POWER)



COLLABORATION SOFTWARE INCLUDED



INCLUDED WIFI MODULE



PRE-INSTALLED BRACKETS

PANEL AUDIO	
Speaker Type	Built-in speakers on top front
Output Power	2 × 8W (speakers) + 2 × 18W (subwoofers)
Sound Channel	2.2
Sound Pressure Level	85dB
Peak Power	2 × 108W
Microphone	8 array up to 32.8 ft distance

PANEL CONNECTIONS	
HDMI Input	3
HDMI Output	1
USB 2.0	1
USB 3.0	4 Front ×2, Rear ×2
USB Type-C Input	3; Front & Side PC input (video, audio, touch, LAN transfer) Top input camera only
USB Type-C Output	1
Touch 2.0	2
Display Port Input	1
Audio Input	3.5 mm
Audio Output	3.5 mm
SPDIF	1
RS232	1
RJ45 Input/Output	1 each

PANEL INTERACTIVITY	
Sensing Type	Hybrid Touch (infrared + elastic wave)
Compatibility	Windows11/Windows10/Windows8/ Windows7/WindowsXP/Linux/ MacOSX/Android/Chrome
Touch Point	16 points touch (Android) 40 points touch (Windows)
Minimum Object Size	2 mm
Touch Tool	Finger, passive infrared pen
Response Time	≤10 ms
Accuracy	±1 mm
Surface Hardness	3mm glass with 9H rating of Mohs standard

PANEL OPERATING SYSTEM	
System Version	Android 13
CPU	A76 × 4 + A55 × 4
GPU	Mali-G610 MP4
RAM	8GB
ROM	64GB

PANEL AMBIENT	
Operation Temperature	32°F – 104°F
Operation Humidity	10% – 90% RH
Storage Temperature	-4°F – 140°F
Storage Humidity	10% – 90% RH
Altitude	Below 16404 ft

POWER	
Power Requirements	100-240V ~ 50/60Hz 5.0A
Standby Power	≤0.5W
Standard Power	280W
Max Power Including internal PC	500W

PHYSICAL SPECIFICATION	
Key Location & Number	Front physical keys, 1
Dimension L*H*D*	67.3" × 40.6" × 3.37"
Dimension (package) L*W*H	73.35" × 8.86" × 45.2"
Net Weight	113.76 lbs
Gross Weight	146.72 lbs
Machine + Wall Mount Thickness	5.2"
Wall-hanging Screw Spec	M8 × 25 mm
VESA	800 × 400 mm

WIFI MODULE (INCLUDED)	
Bluetooth 5.2, Wifi Standard: 802.11 a/b/g/n/ac/ax, no antennas	

ACCESSORIES	
American standard power cord, USB Touch cable (Type A-B), USB Type-C cable, HDMI cable, remote control, writing pens (2), USB Dust plug, AAA batteries (2), Quick Start Guide	

PC MODULE (OPTIONAL)	
Type	Detachable PC module
Model	CTI-PCOPS-PC15-SM
CPU	Intel® Core™ i5 10400T CPU
RAM	DDR4 16GB
SSD	1 × M. 2-2280 SSD NVMe 256GB
Graphics	Intel® UHD Graphics 630
Chipset	Intel® Comet Lake; H510
Sound Card	Integrated High Definition Audio Stereo
Networking Ethernet	10/100/1000MB
WiFi Version	802.11ax
WiFi Frequency	2GHz - 3.6GHz
WiFi Working Distance	0 ~ 147.6 ft 0 ~ 295.3 ft
Bluetooth Version	Bluetooth 2.1; 3.0; 4.0; 5.0
Bluetooth Working Frequency	2.4GHz
Bluetooth Working Distance	0 ~ 32.8 ft

Operating System	Not included	Earphone Output	1
USB 2.0 3.0	4	Microphone Input	1
LAN(RJ45)	1	Display Port Output	1
VGA Output	1	HDMI Output	1

PANEL WARRANTY OPTIONS	
Standard	3 years
Purchase	5 years