













# 2015 REALiS LCOS PROJECTOR LINE-UP

REALiS Pro AV	Installation	<p><b>WUXGA</b> (1920 x 1200)</p> <p><b>REALiS WUX5000 / REALiS WUX5000 D</b> High Resolution Installation</p> <ul style="list-style-type: none"> <li>▶ 5000 Lumens</li> <li>▶ WUXGA Resolution (1920 x 1200)</li> <li>▶ Optional Interchangeable Genuine Canon Lenses (projector does not ship with lens)</li> <li>▶ REALiS WUX5000 D features DICOM® Simulation Mode</li> </ul> 	<p><b>REALiS WUX6000 / REALiS WUX6000 D</b> <b>NEW</b> High Resolution Installation</p> <ul style="list-style-type: none"> <li>▶ 6000 Lumens</li> <li>▶ WUXGA Resolution (1920 x 1200)</li> <li>▶ Optional Interchangeable Genuine Canon Lenses (projector does not ship with lens)</li> <li>▶ REALiS WUX6000 D features DICOM® Simulation Mode</li> </ul> 	
	<p><b>WXGA+</b> (1440 x 900)</p> <p><b>REALiS WX6000 / REALiS WX6000 D</b> High Brightness Installation</p> <ul style="list-style-type: none"> <li>▶ 5700 Lumens</li> <li>▶ WXGA+ Resolution (1440 x 900)</li> <li>▶ Optional Interchangeable Genuine Canon Lenses (projector does not ship with lens)</li> <li>▶ REALiS WX6000 D features DICOM® Simulation Mode</li> </ul> 			
	<p><b>SXGA+</b> (1400 x 1050)</p> <p><b>REALiS SX6000 / REALiS SX6000 D</b> High Brightness Installation</p> <ul style="list-style-type: none"> <li>▶ 6000 Lumens</li> <li>▶ SXGA+ Resolution (1400 x 1050)</li> <li>▶ Optional Interchangeable Genuine Canon Lenses (projector does not ship with lens)</li> <li>▶ REALiS SX6000 D features DICOM® Simulation Mode</li> </ul> 			
	Compact Installation	<p><b>WUXGA</b> (1920 x 1200)</p> <p><b>REALiS WUX400ST / REALiS WUX400STD</b> Short Throw Compact Installation</p> <ul style="list-style-type: none"> <li>▶ 4000 Lumens</li> <li>▶ WUXGA Resolution (1920 x 1200)</li> <li>▶ 0.56:1 Throw Ratio</li> <li>▶ Lens Shift: V: 0-75% / H: ±10%</li> <li>▶ REALiS WUX400ST D features DICOM® Simulation Mode</li> </ul> 	<p><b>WUXGA</b> (1920 x 1200)</p> <p><b>REALiS WUX450 / REALiS WUX450 D</b> High Resolution Compact Installation</p> <ul style="list-style-type: none"> <li>▶ 4500 Lumens</li> <li>▶ WUXGA Resolution (1920 x 1200)</li> <li>▶ 1.39–2.51:1 Throw Ratio</li> <li>▶ Fixed f/2.8 Aperture Lens</li> <li>▶ REALiS WUX450 D features DICOM® Simulation Mode</li> </ul> 	
	<p><b>WXGA+</b> (1440 x 900)</p> <p><b>REALiS WX450ST / REALiS WX450STD</b> Short Throw Compact Installation</p> <ul style="list-style-type: none"> <li>▶ 4500 Lumens</li> <li>▶ WXGA+ Resolution (1440 x 900)</li> <li>▶ 0.57:1 Throw Ratio</li> <li>▶ Lens Shift: V: 0-77% / H: ±10%</li> <li>▶ REALiS WX450ST D features DICOM® Simulation Mode</li> </ul> 	<p><b>WXGA+</b> (1440 x 900)</p> <p><b>REALiS WX520 / REALiS WX520 D</b> High Brightness Compact Installation</p> <ul style="list-style-type: none"> <li>▶ 5200 Lumens</li> <li>▶ WXGA+ Resolution (1440 x 900)</li> <li>▶ 1.43–2.57:1 Throw Ratio</li> <li>▶ Fixed f/2.8 Aperture Lens</li> <li>▶ REALiS WX520 D features DICOM® Simulation Mode</li> </ul> 		
		4000 Lumens	5000 Lumens	6000 Lumens
REALiS Portable	<p><b>SXGA+</b> (1400 x 1050)</p> <p><b>REALiS SX80 Mark II / REALiS SX80 Mark II D</b> Affordable High Performance</p> <ul style="list-style-type: none"> <li>▶ 3000 Lumens</li> <li>▶ SXGA+ Resolution (1400 x 1050)</li> <li>▶ 1:48-2.18:1 Throw Ratio</li> <li>▶ REALiS SX80 Mark II D features DICOM® Simulation Mode</li> </ul> 	<p><b>REALiS SX7 Mark II / REALiS SX7 Mark II D</b> Astounding Color Reproduction</p> <ul style="list-style-type: none"> <li>▶ 4000 Lumens</li> <li>▶ SXGA+ Resolution (1400 x 1050)</li> <li>▶ 1:46-2:43:1 Throw Ratio</li> <li>▶ REALiS SX7 Mark II D features DICOM® Simulation Mode</li> </ul> 		
		3000 Lumens	4000 Lumens	

For more info:  
1-800-OK-CANON (1-800-652-2666)  
pro.usa.canon.com



The REALiS WUX5000 D, REALiS WUX4000 D, REALiS WX6000 D, REALiS SX6000 D, REALiS WX520 D, REALiS WUX450 D, REALiS WUX400ST D, REALiS WX450ST D, REALiS WUX10 Mark II D, REALiS SX7 Mark II D, and REALiS SX80 Mark II D projectors are not cleared or approved for medical diagnosis and should not be used for these purposes.



# 2015 DLP & LCD PROJECTOR LINE-UP

**DLP PORTABLE**

**WXGA**  
(1280 x 800)



**LE-5W**  
Ultra-Portable LED Projector

- ▶ DLP Technology
- ▶ 500 Lumens
- ▶ 1.2:1 Throw Ratio
- ▶ WXGA Resolution (1280 x 800)
- ▶ 3000:1 Contrast Ratio
- ▶ 20,000 Hours Life LEDs
- ▶ HDMI Digital Input
- ▶ Quick On and Off
- ▶ "PC Free" presentations
- ▶ Built-in 2.5 watt Stereo Speakers

500 Lumens



**LV-8235 UST**  
Ultra-Short Throw Projector

- ▶ DLP Technology
- ▶ 2500 Lumens
- ▶ 0.19:1 Short Throw Ratio
- ▶ WXGA Resolution (1280 x 800)
- ▶ Display 80 inch image from only 1.05 feet away
- ▶ HDMI Digital Input
- ▶ 2000:1 Contrast Ratio

2000 Lumens

**NEW**

**LV-WX300**  
Compact Wide-Screen Projector



- ▶ DLP® BrilliantColor™ Technology
- ▶ 3 000 Lumens
- ▶ 1.5-1.65:1 Throw Ratio
- ▶ WXGA Resolution (1280 x 800)
- ▶ HDMI Digital Input
- ▶ 2300:1 Contrast Ratio
- ▶ Up to 6,000 Hours Lamp Life
- ▶ Filter Free
- ▶ 10W Built-in Speaker

3000 Lumens

**NEW**

**LV-WX300ST**  
Compact Short Throw Projector



- ▶ DLP® BrilliantColor™ Technology
- ▶ 3000 Lumens
- ▶ 0.49:1 Short Throw Ratio
- ▶ WXGA Resolution (1280 x 800)
- ▶ HDMI Digital Input
- ▶ 2300:1 Contrast Ratio
- ▶ Up to 6,000 Hours Lamp Life
- ▶ Filter Free
- ▶ 10W Built-in Speaker


3000 Lumens

**DLP & LCD PORTABLE**

**XGA**  
(1024 x 768)

**NEW**


**LV-X300**  
Advanced Portable




- ▶ DLP® BrilliantColor™ Technology
- ▶ 3000 Lumens
- ▶ 1.86-2.04:1 Throw Ratio
- ▶ XGA Resolution (1024 x 768)
- ▶ 1.1x Optical Zoom
- ▶ HDMI Digital Input
- ▶ 2300:1 Contrast Ratio
- ▶ Up to 6,000 Hours Lamp Life
- ▶ Filter Free
- ▶ 10W Built-in Speaker

**NEW**

**LV-X300ST**  
Portable Short Throw



- ▶ DLP® BrilliantColor™ Technology
- ▶ 3000 Lumens
- ▶ 0.61:1 Short Throw Ratio
- ▶ XGA Resolution (1024 x 768)
- ▶ HDMI Digital Input
- ▶ 2300:1 Contrast Ratio
- ▶ Up to 6,000 Hours Lamp Life
- ▶ Filter Free
- ▶ 10W Built-in Speaker




**LV-7490**  
High Brightness

- ▶ LCD Technology
- ▶ 4000 Lumens
- ▶ XGA Resolution (1024 x 768)
- ▶ 1.2x Optical Zoom
- ▶ 2000:1 Contrast Ratio
- ▶ Up to 5,000 Hours Lamp Life
- ▶ Up to 5,500 Hours Filter Life
- ▶ 10W Built-in Speaker

4000 Lumens

**NEW**

**LV-S300**  
Affordability & Reliability



- ▶ DLP® BrilliantColor™ Technology
- ▶ 3000 Lumens
- ▶ 1.86-2.04:1 Throw Ratio
- ▶ SVGA Resolution (800 x 600)
- ▶ 1.1x Optical Zoom
- ▶ 2300:1 Contrast Ratio
- ▶ Up to 6,000 Hours Lamp Life
- ▶ Filter Free
- ▶ 2W Built-in Speaker

3000 Lumens

©2014 Canon U.S.A., Inc. All rights reserved. Not responsible for typographical errors. Specifications subject to change without notice. Products not shown to scale. Canon is a registered trademark of Canon Inc. in the United States and may also be a trademark or registered trademark in other countries. REALiS is a trademark of Canon. DICOM is the registered trademark of the National Electrical Manufacturers Association for its standards publications relating to digital communications of medical information. All other products and brand names may be registered trademarks, trademarks or service marks of their respective owners in the United States and/or other countries.