



XJ-UT351WN

1280 x800

XJ-UT351W / WN

ULTRA SHORT THROW SERIES

Native Resolution

LampFree. MercuryFree. StressFree.

Casio's Ultra Short Throw LampFree® projectors incorporate Laser & LED Technology to produce images of impressive brightness. They have a long lasting lifespan of up to 20,000 hours with reduced electricity consumption and no lamps or filters to replace.

With their Ultra-Short Throw lens, the XJUT351W and XJ-UT351WN can project brilliant, crisp, shadow-free images of up to 110" diagonal with a full assortment of connectivity and features. The built-in short throw lens and advanced mirror system provides an extremely close throw ratio (0.28:1) and projects an 80" image from just 1.5 feet away.

Key Features

- 3500 Lumens
- · Ultra Short Throw Ratio (.28:1)
- Dust Resistant Design
- Built-in 16W speaker
- Expanded input/output connectivity
- High Contrast Ratio of 20,000:1
- DLP® Technology

LampFree Features

- Laser & LED Hybrid Light Source
- · Long Life, 20,000 hour estimated operating life
- No Lamp replacement required
- No Filters
- Less Down Time
- Low Power Consumption
- Mercury Free
- Quick On (5 seconds to full brightness)
- Instant Off no cool down required

XJ-UT351WN Only

- RJ-45 Wired LAN
- · Wireless Capability
- · Optional Wireless Adaptor (YW-40) Available



Native Aspect Ratio Brightness 3500 lumens Display Device 0.65" DLP® chip Contrast Ratio 20.000:1 Fixed Zoom/Manual Focus Lens Type Fixed lens F2.3/f4.2 70% Lens Offset Laser & LED (Up to 20,000 Hours) Light Source Projection Screen Size (Min-Max) 50 to 110-inch diagonal 60-inch screen 0.4 ft 1.3 ft 0.2 ft Throw Ratio (60 inches) 0.28:1 Keystone Correction Vertical and Horizontal + or - 5° (Manual) Full color (1.07 billion colors) Power Consumption 185W Operating (Minimum) Light Output 1 Operating (Bright) 125W Standby (Remote Off/On) 0.23 W/2.6 W TERMINAL CONNECTIVITY Maximum Signal Input WUXGA (1920 x 1200) Analog input terminal mini D-Sub 15 pin x 2 mini D-Sub 15 pin x1 Also use as YCbC;/YPbPr input— commercially available adapter required HDMI Type A x2 (480p-1080p) RGB/Component Video Input HDMI Input USB Input USB 2.0 Type A x 1 Video (RCA) x1, S Video x 1 Composite Video Input RCA (R/L) x1, Stereo Mini x 2 DC 5V / 2A Audio Input USB Power Supply Microphone Input Built-in Memory Logo Transfer USB 1.1 Micro-B x 1 Audio Output Stereo Mini x 1, Mini D-sub 15 pin x 1 Monitor Output mini D-Sub 15 pin x 1 RS-232C (D sub 9 pin) x 1 Cross Cable (Null Modem) required Control (Serial) Terminal Built in Speaker Optional Wireless LAN Adapter (YW-40) Wireless Capability Available OTHER INFORMATIC Operating Temperature 41º - 95º F Operating Humidity Remote Control Operating Range 20% - 80% (non-condensation) 16.4 ft Max. Kensington / Power On Password Product Dimension (W x D x H) Yes 16.5 x 13.1 x 6.0 inches Weight 13.23lbs Packing Information Carton Dimensions 20.9 x 16.2 x 10.2 inches Remote control, 6' RGB cable, 6' AC Power Cord Included Accessories

Terminal Interface

Mounting Screws

UPC Code





M4 x 4 (not included) Insert depth (5-8 mm)
800431 889232800448

XJ-UT351W

XJ-UT351WN

Designed and Manufactured by Casio in Japan TAA Compliant

© 2017 Casio America, Inc. All rights reserved. Casio is a registered trademark of Casio Computer Co., Ltd. In the United States and/or other countries. Specifications were thought to be correct at time of publication. All specifications and features are subject to change without notice. DLP, the DLP logo and the DLP medallion are trademarks of Texas Instruments. XGA is registered trademark of International Business Machines Corporation in the United States. HDMI is a trademark or registered trademark of HDMI Licensing, LtC. Other product names or company names on this specification brochure are either trademarks or registered trademarks of their respective owners.

889232800431