



NOTE:
 AT SYSTEM LOAD OF 0LBS, DISTANCE = 2.47IN
 AT SYSTEM LOAD OF 50LBS, DISTANCE = 2.80IN
 AT SYSTEM LOAD OF 100LBS, DISTANCE = 2.90IN

DISTANCE: TOP OF FIRST COLLAR TO BOTTOM OF SECOND COLLAR
SYSTEM LOAD: TOTAL LOAD BELOW SECOND COLLAR

THE INFORMATION AND DESIGNS CONTAINED IN THIS DRAWING ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF MILESTONE AV TECHNOLOGIES NEITHER THIS DESIGN NOR ANY INFORMATION CONTAINED IN THIS DRAWING MAY BE REPRODUCED OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF MILESTONE AV TECHNOLOGIES.

CAD GENERATED DRAWING, DO NOT MANUALLY UPDATE.			CHIEF	6436 CITY WEST PKWY EDEN PRAIRIE MN, 55344 PHONE: 866-977-3901 FAX: 877-894-6918	
DRAWN BY	CT	5/29/2018		DESCRIPTION	XL VIBRATION ISOLATOR COUPLER
ENG APPROVAL			MODEL NO.	CMA348	
MFG APPROVAL			SIZE	DWG. NO.	REV.
QA APPROVAL			B	TECH-000932	00
SHEET 1 OF 1			SCALE	1:8	