



TILT WALL MOUNTS LTM □ 37 - 63" MICRO-ADJUSTABLE TILT MOUNT

FUSION® SERIES



FEATURES

- 1 CONTROLZONE™ LEVELING**
Industry-first feature allows post-installation fine tuning of height and leveling, up to 0.5" (13 mm) adjustment up or down.
- 2 CENTRIS® LOW-PROFILE TILT**
Centris fingertip tilt technology uses the center of gravity to balance the screen while maintaining a low profile under 2" (51 mm) deep! Screen angle stays set in place until readjusted.
- 3 CENTERLESS™ SHIFT**
Provides up to 17.5" (445 mm) of post-installation lateral shift - 8.75" (222 mm) left/right of uprights - for limitless centering capabilities.
- 4 CLICKCONNECT™**
Hear an audible click when the screen safely engages with the mount. A built-in cable stand provides easy access under the screen.

WHAT YOU NEED TO KNOW

MULTIPLE INSTALLATION AND ORDERING OPTIONS

Can be installed on 12" on-centers up to 32". For a complete installation order the LTMUP Tilt Mount and Power Conditioner Kit (includes LTMU and PAC521P).

OTHER PRODUCT OPTIONS



LTA
FUSION Wall Mount
- For flat panels 37-63"



RLT2
FIT™ Hinge Mount
- For flat panels 32-52"



PWC
Tilt Wall Mount with
CPU Storage



RXT2
FIT™ Hinge Mount
- For flat panels 40-63"

SPECIFICATIONS

Depth from Wall	1.98" (50 mm)
Tilt*	-12°
Max Lateral Shift	17.5" (445 mm)
Dimensions (HxWxD)	16.5 x 34.44 x 1.99" (419 x 875 x 51 mm)
Max Mounting Pattern (H,W)	19.88" (505 mm) 35.35" (895 mm)
Color	Black
Weight Capacity	200 lbs (90.7 kg)

*Varies with screen height.

RECOMMENDED ACCESSORIES



FVS250 ■ 12" (305 mm) Video Conferencing Shelf - above



FCS100 ■ Single Component Shelf - below



FLR100 ■ Left/Right Speaker Adapter

For a complete list of FUSION accessories see pages 86 - 88.

TECHNICAL DRAWINGS

