

# INSTALLATION INSTRUCTIONS

## JUNCTION BOX ASSEMBLY CEILING PLATE

### CMA-106

The Ceiling Plates are designed for ease of installation with any height of ceiling. By using any length of standard NPT 1½” pipe threaded both ends, you can extend the height capabilities to meet your needs.

**WARNING: IMPROPER INSTALLATION MAY RESULT IN SERIOUS PERSONAL INJURY!**

When mounting Chief Manufacturing accessories, the structural system and mounting method **MUST** be capable of supporting 5 times the combined weight of the total installation.

The maximum weight to be installed on the ceiling plate is 50 pounds (22.7 Kg).

Unpack and check contents:

- |                         |                                |
|-------------------------|--------------------------------|
| (1) Ceiling Plate       | (2) #10 Fender Washer          |
| (2) #10-32 Socket Screw | (2) #10 Lock Washer            |
| (1) 1/8” Hex Key        | (1) #10-24 x 1/4” Socket Screw |
| (1) 3/32” Hex Key       |                                |

1. Securely install the Junction Box Assembly, per manufacturer instruction. (**SEE WARNING ABOVE**).
2. Using the #10-32 screws, fender washers, lock washers and hex key provided, install ceiling plate (**SEE DIAGRAM BELOW**).
3. Install 1 ½” NPT into fitting and secure using #10-24 x 1/4” set screw.
4. Follow the Ceiling Mount Instructions for mating components or mounts

