
## Christie Vive Audio S Series S118LP low profile subwoofer



<sup>=</sup>ront view



## Side view



## Top view



## Back view



System type	Subwoofer, ported enclosure, with EBS (Extended Bass Shelf) tuning				
Driver components	• 18" low frequency driver with dual 4" voice coils and long linear excursion				
Crossover	<ul> <li>External active electronic bandpass filter is required for proper operation</li> <li>High pass: Butterworth 24dB/octave @ 20Hz</li> <li>Low pass: Bessel 24dB/octave @ 250Hz</li> </ul>				
Frequency response <sup>1</sup>	• 20-250Hz @ -10dB • 24-200Hz @ -6dB				
Maximum SPL <sup>2,3</sup>	• 127.5dB SPL continuous • 139.5dB SPL peak				
Sensitivity <sup>1</sup> , 1W/1m	• 97.5dB (40-150Hz)				
Power handling <sup>2,3</sup>	• 1000W (AES) continuous • 2000W (IEC) short term				
Recommended amplifier power	• 825-1150W (FTC) @ 8 ohms				
Rated impedance	• 8 ohms				
Input connectors	Screw terminal barrier strip				
Enclosure	<ul> <li>Premium MDF cabinet</li> <li>High cubic displacement</li> <li>Heavily cross-braced for minimal enclosure resonance</li> <li>Ported and tuned to 23Hz with EBS</li> <li>Two built-in handles</li> </ul>				
Mounting	<ul> <li>Secured to floor or platform using suitable lag bolts as required</li> <li>Not to be flown</li> </ul>				
Dimensions	• (LxWxH) 40.8 x 15.5 x 30" (1037 x 394 x 762mm)				
Net weight	• 93lbs (42kg)				
Warranty	Limited 5-year warranty				

<sup>1</sup> Rated for free space conditions at 1m.

Measured at 2m, ground plane conditions, with value calculated for free space conditions at 1m.

<sup>2</sup> AES refers to AES2-2012 standard. Pink noise with 6dB crest factor at 1m.

Max continuous SPL calculated based on sensitivity and AES power handling.

<sup>3</sup> IEC refers to IEC 60268-5 standard. IEC pink noise with 9dB peak factor.

Maximum peak SPL calculated using peak voltage during IEC short-term power test.

Corporate offices	Worldwide offices					
Christie Digital Systems USA, Inc. Cypress ph: 714 236 8610 Christie Digital Systems Canada Inc. Kitchener ph: 519 744 8005	Australia ph: +61 (0) 7 3624 4888	France ph: +33 (0) 1 41 21 44 04	Republic of South Africa ph: +27 11 251 0000	United States (Arizona) ph: 602 943 5700	System ♦ ♦ ≋	
	Brazil ph: +55 (11) 2548 4753	Germany (Cologne) ph: +49 221 99 512-0	Singapore ph: +65 6877 8737	United States (New York) ph: 646 779 2014	Certified System	
	China (Beijing) ph: +86 10 6561 0240	Germany (Moechengladbach) ph: +49 2161 566200	South Korea ph: +82 2 702 1601	Independent sales consultant offices	ISO 900 <sup>-</sup> ISO 1400	
	China (Shanghai) ph: +86 21 6030 0500	India ph: +91 (080) 6708 9999	Spain ph: +34 91 633 9990	ltaly ph: +39 (0) 2 9902 1161 Russia ph: +7 (495) 930 8961	Kitchener, Ontario	
	Columbia ph: +57 (318) 447 3179	Japan ph: +81 3 3599 7481	United Arab Emirates ph: +971 (0) 4 503 6800			
	Eastern Europe ph: +36 (0)1 47 48 138	Mexico ph: +52 55 4744 1790	United Kingdom ph: +44 (0) 118 977 8000			

For the most current specification information, please visit www.christiedigital.com

Copyright 2018 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. Printed in Canada on recycled paper. 4654 Feb 18

