

Christie Access Series LCD panels

The perfect balance between performance and price

Technical specifications		Christie UHD551-L	Christie UHD651-L
Display technology	screen size (diagonal)	• 55"/139.7cm	• 65"/165.1cm
	native resolution	• UHD 3840 x 2160 (16:9)	
	backlight	• Edge-lit LED	
	LED lifespan	• 50,000 hours to 50% brightness	
	display orientation	• Landscape	
	pixel pitch	• 0.315 x 0.315mm	• 0.372 x 0.372mm
	nominal bezel size (bottom/side/top)	• 14mm/11mm/11mm	• 21mm/15mm/15mm
	brightness	• 400 nits (cd/m ²) typical	
	contrast ratio (full field)	• 1200:1 typical	• 4000:1 typical
	viewing angle (CR 10:1)	• 178° h/v	
	refresh rate	• 60Hz	
	response time	• 8 ms typical	
	color space (CIE 1931)	• 68% typical	• 75% typical
	display colors	• 10 bit, 1.07 billion colors	• 8 bit, 16.7 million colors
Video	inputs	• 2 x HDMI (Ver 2.0, HDCP 2.2) • DisplayPort (Ver 1.2a, HDCP 1.3) • VGA • YPbPr • 2 x USB 2.0 • USB 3.0	
	outputs	• DisplayPort 1.2a; HDMI 2.0	
Audio	inputs	• RCA (L/R) line in	
	outputs	• RCA (L/R) line out • 3.5mm headphone jack • SPDIF coax	
Control	inputs	• RS-232 (D-Sub9) • LAN (RJ45) • IR wire extender	
Power	input rating	• 100-240 VAC @ 50-60Hz	
	power consumption	• 70W typical without OPS • 140 W maximum without OPS • <=0.5W in standby without OPS	• 73W typical without OPS • 140W maximum without OPS • <=0.5W in standby without OPS
Environment	operating temperature	• 32-104°F (0-40°C)	
	storage temperature	• -4-140°F (-20-60°C)	
	operating humidity	• 20-90% RH non-condensing	
Physical	size (panel only)	• (WxHxD) 48.7 x 28 x 4.1" (1238 x 712 x 104mm)	• (WxHxD) 57.4 x 33.1 x 3.8" (1459 x 841 x 96mm)
	weight	• 38.6lbs (17.5kg)	• 49.6lbs (22.5kg)
	mounting	• VESA 400 x 200mm, M6	• VESA 400 x 400mm, M6
Runtime	• Designed for 16/7 operation featuring a reliable power supply ¹		
Features	• Commercial grade LCD with LED backlight • OPS slot • Anti-glare treatment • 2 x 8W speakers • On/off scheduler • USB playback of Photo/Video/MP3 • HDMI-CEC • Source switching for failover • Kensington lock • Wi-Fi® • Bluetooth • Miracast device connectivity • Pixel shifting		
Accessories	• Panel ships with IR remote control • External IR receiver • Power cable • User manual • Optional TA551 up to 10 point IR touch overlay (for 55") and TA651 up to 10 point IR touch overlay (for 65")		
Warranty	• Three year parts and labor limited warranty • Contact an authorized Christie representative for full details		

¹ Avoid static images for extended periods. Refer to the user manual for additional runtime guidelines.

Content and operating conditions can affect the useful life of the product. Please refer to the product user manual and Christie Operating Guidelines for Flat Panels, available at www.christiedigital.com

Touchboards

205 Westwood Ave, Long Branch, NJ 07740
 Phone: 866-94 BOARDS (26273) / (732)-222-1511
 Fax: (732)-222-7088 | E-mail: sales@touchboards.com

Corporate offices

Christie Digital Systems USA, Inc.
 Cypress
 ph: 714 236 8610

Christie Digital Systems Canada Inc.
 Kitchener
 ph: 519 744 8005

Worldwide offices

Australia
 ph: +61 (0) 7 3624 4888

Brazil
 ph: +55 (11) 2548 4753

China (Beijing)
 ph: +86 10 6561 0240

China (Shanghai)
 ph: +86 21 6278 7708

France
 ph: +33 (0) 1 41 21 44 04

Germany
 ph: +49 2161 664540

India
 ph: +91 (080) 6708 9999

Japan (Tokyo)
 ph: 81 3 3599 7481

Korea (Seoul)
 ph: +82 2 702 1601

Mexico
 ph: +52 55-4744-1790

Republic of South Africa
 ph: +27 11 251 0000

Russian Federation
 and Eastern Europe
 ph: +36 (0) 1 47 48 100

Singapore
 ph: +65 6877 8737

Spain
 ph: +34 91 633 9990

United Arab Emirates
 ph: +971 4 3206688

United Kingdom
 ph: +44 (0) 118 977 8000

United States (Arizona)
 ph: 602 943 5700

United States (New York)
 ph: 646 779 2014

**Independent sales
 consultant offices**

Italy
 ph: +39 (0) 2 9902 1161



For the most current specification information, please visit www.christiedigital.com

Copyright 2017 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. Printed in Canada on recycled paper. 4503 May 17

CHRISTIE®