

Christie Terra Transmitter

Technical specifications		Christie TXO 102 SO (166-001102-01)
Video in		<ul style="list-style-type: none"> • One switchable input: HDMI or DisplayPort • Input format: HDMI 2.0a, DisplayPort 1.2 • Content protection: HDCP 2.2 compliant • Maximum resolution: 4096 x 2160, 60Hz, 8-bit 4:4:4, 10-bit 4:2:2, 10-bit and 12-bit 4:2:0 • HDR, 3D and Deep Color pass through support • Maximum bandwidth: 594 MHz
Audio in		<ul style="list-style-type: none"> • Analog stereo: line level, 3.5mm stereo mini-jack • HDMI embedded audio: multi-channel PCM, Dolby True HD, DTS-HD Master Audio
Routeable control ports		<ul style="list-style-type: none"> • Serial RS-232: 9-PinD, up to 115.2K baud • Wired IR in: 3.5mm stereo mini-jack • Wired IR out: 3.5mm DC mini-jack • USB 2.0: type-B plug • Ethernet (1000BaseT) RJ45
Video processing		<ul style="list-style-type: none"> • Video is uncompressed, except 4K/60 input formats including 8-bit 4:4:4, 10-bit 4:2:2, 10-bit and 12-bit 4:2:0. Ultra-lightweight 1.3-to-1 compression ratio is used for these formats which is artifact-free • Color space, bit depth and frame rate conversion • Broadcast quality down-scaling and up-scaling
Latency		<ul style="list-style-type: none"> • Zero-frame latency mode: < 100µs, see reference guide for details
Network		<ul style="list-style-type: none"> • Content transport and control: 10G Ethernet, SFP+ • Optional Control: 1000BaseT Ethernet, RJ45 • Protocols: IP, TCP, UDP, IPv4, IGMPv2 • Content encryption: AES 128-bit
Front panel LED indicators		<ul style="list-style-type: none"> • Link validation for: video signal, transmit, receive, 1G Ethernet, USB, power • Button 1: switch input • Button 2: programmable (future)
Dimensions		<ul style="list-style-type: none"> • (WxHxD) 8.41 x 1.66 x 6.22" (213.5 x 42 x 158mm) case only • (WxHxD) 8.41 x 1.66 x 6.50" (213.5 x 42 x 165mm) including connectors
Sound pressure		<ul style="list-style-type: none"> • Less than 38dBA on a tabletop from a distance of 0.5m (typical)
Material		<ul style="list-style-type: none"> • Steel, painted black
Environment	operating temperature	<ul style="list-style-type: none"> • 32-104°F (0-40°C)
	storage temperature	<ul style="list-style-type: none"> • -4-140°F (-20-60°C)
	operating humidity	<ul style="list-style-type: none"> • 20-90% RH (non-condensing)
External power supply	input	<ul style="list-style-type: none"> • 100-240 VAC @ 50-60Hz
	output	<ul style="list-style-type: none"> • 12V DC, 3.0A, 36W maximum
	typical operation	<ul style="list-style-type: none"> • 10W, 35 BTU
Weight		<ul style="list-style-type: none"> • 2.3lbs (1.1kg) excluding power supply • 2.8lbs (1.3kg) with power supply
Reliability		<ul style="list-style-type: none"> • MTBF > 50,000 hours • MTTR < 15 minutes
Regulatory		<ul style="list-style-type: none"> • CE/FCC Class A, Directives (EC) 2011/65/EU (RoHS), 2012/19/EU (WEEE), Regulation (EC) No. 1907/2006 (REACH)
Manufacturing location		<ul style="list-style-type: none"> • Designed and developed in Canada, USA and Taiwan • Manufactured in Taiwan
Warranty		<ul style="list-style-type: none"> • Limited two years parts and labor
UPC		<ul style="list-style-type: none"> • 723466962605

Corporate offices

Christie Digital Systems USA, Inc.
Cypress
ph: 714 236 8610

Christie Digital Systems Canada Inc.
Kitchener
ph: 519 744 8005

Worldwide offices

Australia
ph: +61 (0) 7 3624 4888

Brazil
ph: +55 (11) 2548 4753

China (Beijing)
ph: +86 10 6561 0240

China (Shanghai)
ph: +86 21 6030 0500

Columbia
ph: +57 (318) 447 3179

Eastern Europe
ph: +36 (0)1 47 48 138

France
ph: +33 (0) 1 41 21 44 04

Germany (Cologne)
ph: +49 221 99 512-0

Germany (Moechengladbach)
ph: +49 2161 566200

India
ph: +91 (080) 6708 9999

Japan
ph: +81 3 3599 7481

Mexico
ph: +52 55 4744 1790

Republic of South Africa
ph: +27 11 251 0000

Singapore
ph: +65 6877 8737

South Korea
ph: +82 2 702 1601

Spain
ph: +34 91 633 9990

United Arab Emirates
ph: +971 (0) 4 503 6800

United Kingdom
ph: +44 (0) 118 977 8000

United States (Arizona)
ph: 602 943 5700

United States (New York)
ph: 646 779 2014

Independent sales
consultant offices

Italy
ph: +39 (0) 2 9902 1161

Russia
ph: +7 (495) 930 8961



For the most current specification information, please visit www.christiedigital.com