

# Christie

## Access II Series LCD panels

Full-featured UHD displays for meeting rooms and digital signage

Technical specifications		UHD552-L	UHD652-L
Display technology	screen size (diagonal)	• 55"/139.7cm	• 65"/165.1cm
	native resolution	• UHD 3840 x 2160 (16:9)	
	backlight	• LED Edge-lit	
	LED lifespan	• 50,000 hours to 50% brightness	
	display orientation	• Landscape	
	pixel pitch	• 0.315 x 0.315mm	• 0.372 x 0.372mm
	nominal bezel size (bottom/side/top)	• 12mm/7mm/7mm	• 13mm/10mm/10mm
	brightness	• 500 nits (cd/m <sup>2</sup> ) typical	
	contrast ratio (full field)	• 1200:1 typical	• 1200:1 typical
	viewing angle (CR 10:1)	• 178° h/v	
	refresh rate	• 60Hz	
	response time	• 8ms typical	
	color space (CIE 1931)	• 68% typical	• 75% typical
	display colors	• 10 bit, 1.07 billion colors	
Video	inputs	• 4 x HDMI™ (Ver 2.0, HDCP 2.2) • DisplayPort (Ver 1.2a, HDCP 1.3) • VGA • OPS • USB C • 2 x USB 2.0	
	outputs	• DisplayPort™ 1.2a; HDMI 2.0	
Audio	inputs	• RCA (L/R) line in	
	outputs	• 3.5mm headphone jack • Optical Audio Out	
Control	inputs	• RS-232 (D-Sub9) • LAN (RJ45) • IR wire extender	
Power	input rating	• 100-240 VAC @ 50-60Hz	
	power consumption	• 70W typical without OPS • 140W maximum without OPS • <=0.5W in standby without OPS	• 73W typical without OPS • 140W maximum without OPS • <=0.5W in standby without OPS
Environment	operating temperature	• 32-104°F (0-40°C)	
	storage temperature	• -4-140°F (-20-60°C)	
	operating humidity	• 20-90% RH non-condensing	
Physical	size (panel only)	• (WxHxD) 48.7 x 28 x 2.5" (1236 x 710 x 63mm)	• (WxHxD) 57.3 x 32.8 x 2.8" (1455 x 834 x 71mm)
	weight	• 38.6lbs (17.5kg)	• 54.5lbs (24.7kg)
	mounting	• VESA 400 x 400mm, M6	• VESA 600 x 400mm, M6
Runtime		• Designed for 16/7 operation featuring a reliable power supply <sup>1</sup>	
Features		• Commercial LCD with LED backlight • HDR10 support • Failover auto source switching • Video wall mode • Low latency video processing option • Wake on LAN • On/off scheduling • 2 x 10W Built-in speakers • OPS module slot • On/Off Scheduler • USB Media playback of Photo/Video/MP3 • HDMI-CEC • Kensington lock • WiFi and Miracast Ready • Pixel Shifting	
Accessories		• Panel ships with IR remote control • External IR receiver • Power cable • User manual • Optional WiFi Module <sup>2</sup>	
Warranty		• Three years parts and labor limited warranty • Contact an authorized Christie representative for full details	

<sup>1</sup> Avoid static images for extended periods. Refer to the user manual for additional runtime guidelines.

<sup>2</sup> WiFi capability is provided via optional USB dongle

Content and operating conditions can affect the useful life of the product. Please refer to the product user manual and available at [www.christiedigital.com](http://www.christiedigital.com)

For the most current specification information, please visit [christiedigital.com](http://christiedigital.com)

Copyright 2020 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. "Christie" is a trademark of Christie Digital Systems USA, Inc., registered in the United States of America and other countries. DLP® and the DLP logo are registered trademarks of Texas Instruments. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. CD1496\_Christie Access Series\_UHD552-L\_UHD652-L\_SpecSheet\_Aug-20\_EN



**CHRISTIE**®