

Christie Access Series LCD panels

The perfect balance between performance and price

Technical specifications		UHD551-L	UHD651-L	UHD861-LT with integrated touch
Display technology	screen size (diagonal)	• 55"/139.7cm	• 65"/165.1cm	• 86"/218.4cm
	native resolution	• UHD 3840 x 2160 (16:9)		
	backlight	• Direct-lit LED		
	LED lifespan	• 50,000 hours to 50% brightness		
	display orientation	• Landscape		
	pixel pitch	• 0.315 x 0.315mm	• 0.372 x 0.372mm	• 0.4935 x 0.4935mm
	nominal bezel size (bottom/side/top)	• 14mm/11mm/11mm	• 21mm/15mm/15mm	• 38mm/38mm/38mm
	brightness	• 400 nits (cd/m ²) typical		• 410 nits (cd/m ²) typical
	contrast ratio (full field)	• 1200:1 typical	• 4000:1 typical	• 1200:1 typical
	viewing angle (CR 10:1)	• 178° h/v		• 89° h/v
	refresh rate	• 60Hz		
	response time	• 8ms typical		
	color space (CIE 1931)	• 68% typical	• 75% typical	• 72% typical
	display colors	• 10 bit, 1.07 billion colors		
Video	inputs	• 2 x HDMI (Ver 2.0, HDCP 2.2) • DisplayPort (Ver 1.2a, HDCP 1.3) • VGA • YPbPr • USB 3.0		• 1 x USB 2.0 • 1 internal USB 2.0 behind door with screw lock • OPS
	outputs	• DisplayPort 1.2a; HDMI 2.0		
Audio	inputs	• RCA (L/R) line in		
	outputs	• RCA (L/R) line out • 3.5mm headphone jack • SPDIF coax		
Control	inputs	• RS-232 (D-Sub9) • LAN (RJ45) • IR wire extender		
Power	input rating	• 100-240 VAC @ 50-60Hz		
	power consumption	• 70W typical without OPS • 140W maximum without OPS • <=0.5W in standby without OPS	• 73W typical without OPS • 140W maximum without OPS • <=0.5W in standby without OPS	• 276W typical without OPS • 360W maximum without OPS • <=0.5W in standby without OPS
Environment	operating temperature	• 32-104°F (0-40°C)		
	storage temperature	• -4-140°F (-20-60°C)		
	operating humidity	• 20-90% RH non-condensing		
Physical	size (panel only)	• (WxHxD) 48.7 x 28 x 4.1" (1238 x 712 x 104mm)	• (WxHxD) 57.4 x 33.1 x 3.8" (1459 x 841 x 96mm)	• (WxHxD) 77.8 x 45.1 x 4.1" (1975 x 1146 x 103mm)
	weight	• 38.6lbs (17.5kg)	• 54.5lbs (24.7kg)	• 202lbs (92kg)
	mounting	• VESA 400 x 200mm, M6	• VESA 400 x 400mm, M6	• VESA 600 x 400mm, M8
Runtime	• Designed for 16/7 operation featuring a reliable power supply ¹			
Features	• Commercial-grade LCD with edge-lit LED backlight • OPS slot • Anti-glare treatment • 2 x 8W speakers • On/off scheduler • USB playback of Photo/Video/MP3 • HDMI-CEC • Source switching for failover • Kensington lock ² • Wi-Fi ^{®2} • Bluetooth ² • Miracast device connectivity ² • Pixel shifting			
Accessories	• Panel ships with IR remote control • External IR receiver • Power cable • User manual • Optional TA551 up to 10 point IR touch overlay (for 55") and TA651 up to 10 point IR touch overlay (for 65")			
Warranty	• Three years parts and labor limited warranty • Contact an authorized Christie representative for full details			
Detection method				• Infrared rays
Touch interactivity	capability	• Via optional touch overlay TA551	• Via optional touch overlay TA651	• Integrated touch included
	supported touch points			• 10 maximum (simultaneous over 90% area)
	object size recognized			• Single touch 5mm minimum • Multi drawing 5mm minimum
	touch response rate			• Typ 3-10 ms
	supports the following OS			• Windows [®] 7/8/10 • Mac [®] OS ³

¹ Avoid static images for extended periods. Refer to the user manual for additional runtime guidelines.

² For UHD861-LT: WiFi capability is provided via USB dongle; Kensington lock, Miracast connectivity and Bluetooth are not applicable. ³ Single touch for Mac OS.

Content and operating conditions can affect the useful life of the product. Please refer to the product user manual and Christie Operating Guidelines for Flat Panels, available at www.christiedigital.com

Corporate offices

Christie Digital Systems USA, Inc.
Cypress
ph: 714 236 8610

Christie Digital Systems Canada Inc.
Kitchener
ph: 519 744 8005

Worldwide offices

Australia
ph: +61 (0) 7 3624 4888

Brazil
ph: +55 (11) 2548 4753

China (Beijing)
ph: +86 10 6561 0240

China (Shanghai)
ph: +86 21 6030 0500

Colombia
ph: +57 (318) 447 3179

Eastern Europe
ph: +36 (0)1 47 48 138

France
ph: +33 (0) 1 41 21 44 04

Germany (Cologne)
ph: +49 221 99 512-0

Germany (Mönchengladbach)
ph: +49 2161 566200

India
ph: +91 (080) 6708 9999

Japan
ph: +81 3 3599 7481

Mexico
ph: +52 55 4744 1790

Republic of South Africa
ph: +27 11 251 0000

Singapore
ph: +65 6877 8737

South Korea
ph: +82 2 702 1601

Spain
ph: +34 91 633 9990

United Arab Emirates
ph: +971 (0) 4 503 6800

United Kingdom
ph: +44 (0) 118 977 8000

United States (Arizona)
ph: 602 943 5700

United States (New York)
ph: 646 779 2014

Independent sales consultant offices

Italy
ph: +39 (0) 2 9902 1161

Russia
ph: +7 (495) 930 8961



Christie System
ISO 9001
ISO 14001
Kitchener, Ontario

For the most current specification information, please visit www.christiedigital.com

Copyright 2018 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. Printed in Canada on recycled paper. 4711 Aug 18

CHRISTIE[®]