



PRODUCT SPECIFICATIONS

75" 6000K+ Series



75" Panel Specifications

Size	75 in
Screen Type	LED
Aspect Ratio	16:9
Display Area	64.97 in x 36.55 in
Resolution	3840(H) x 2160(V) Ultra HD
Pixel Pitch	.4296 mm x .4296 mm
Back Light Unit	Direct type LED
Response Time	8.5 ms
Refreshing Frequency	60Hz
Display Color	1.07B (10 bit)
Brightness	350 cd/m ²
Contrast Ratio	4000:1
Viewing Angle	178°
Life Time	≥30000 hours

6000K+ SERIES INTERACTIVE PANELS

Collaborative panels for flexible environments.



DUAL ETHERNET PORT



2+1 AUDIO SYSTEM



USB-C CABLE (AUDIO, VIDEO, TOUCH, AND POWER)



COLLABORATION SOFTWARE WITHOUT SUBSCRIPTION



INCLUDED WIFI MODULE



PRE-INSTALLED BRACKETS

PANEL AUDIO

Speaker Type	Built-in speaker
Output Power	2 x 10W+15W
Sound Channel	2.1

PANEL CONNECTIONS

HDMI Output (Configurable)	1
USB 2.0	1
USB 3.0	4
Touch Output	2
HDMI Input	3
USB Type-C	1
VGA Input	1
PC Audio In	1
RS232 Port	1
Audio Output	1
RJ45 Port	2
SPDIF	1

PANEL INTERACTIVITY

Sensing Type	Infrared recognition
Compatibility	Windows10/Windows8/Windows7/ WindowsXP/Linux/MacOSX/ Android/Chrome
Touch Point	10 points writing 20 points touch
Minimum Object Size	3 mm
Touch Tool	Finger, passive infrared pen
Response Time	<10 ms
Accuracy	±1 mm
Communication Mode	Full-speed USB
Interface	USB
Touch Drive	Free drive
Surface Hardness	Toughened glass with Level 7 of Mohs standard
Output Coordinate	32768 x 32768

PANEL OPERATING SYSTEM

System Version	Android 9.0
CPU	A73 x 4
GPU	G52MC2
RAM	4GB
ROM	32GB

PANEL AMBIENT

Operation Temperature	32°F – 104°F
Operation Humidity	10% – 90%
Storage Temperature	-4°F – 140°F
Storage Humidity	10% – 90%
Altitude	Below 16000 ft

POWER

Power Requirements	100-240V ~ 50/60Hz
Standby Power	≤0.5W
Overall Power (nominal power)	550W

PHYSICAL SPECIFICATION

Key Location & Number	Front physical keys, 1
Dimension L*H*D	67.28 in x 40.16 in x 3.39 in
Dimension (package) L*W*H	73.23 in x 11.02 in x 44.88 in
Net Weight	112.77 lbs.
Gross Weight	149.91 lbs.
Machine + Wall Mount Thickness	4.57 in WIB9060G
Wall-hanging Screw Spec	M8 x 25 mm
VESA	800 x 400 mm

WIFI MODULE (INCLUDED)

Bluetooth 5.0, no antennas

ACCESSORIES

American standard power cord, USB touch cable (Type A-B), HDMI cable, remote control, writing pens (2), AAA batteries (2), Quick Start Guide

PC MODULE (OPTIONAL)

Type	Detachable PC module
Model	CTI-PCMOD-PC45-ST-i5 CTI-PCMOD-PC47-IG-i7 CTI-PCMOD-PC47-VP-i7
CPU	Intel® Core™ i5 8400 CPU Intel® Core™ i7 8700 CPU
RAM	DDR4 8GB DDR4 16GB
SSD	128GB 256GB
Graphics	Integrated Intel® HD UHD Graphics 630 GT 1030 Independent Graphics
Chipset	Intel® H310 Intel® Q370
Sound Card	Integrated High Definition Audio Stereo
Networking	10/100/1000MB
WiFi Version	802.11
WiFi Frequency	2.4GHz
WiFi Working Distance	0 ~ 10m
Bluetooth Version	Bluetooth 2.1; 3.0; 4.0; 5.0
Bluetooth Working Frequency	2.4GHz
Bluetooth Working Distance	0 ~ 10m
Operating System	Not included
USB 2.0 3.0	6
LAN(RJ45)	1
VGA Output	1
Earphone Output	1
Microphone Input	1
Display Port Output	1
HDMI Output	1

PANEL WARRANTY OPTIONS

Standard	1 year
Registered	3 year
Optional	5 year