



PRODUCT SPECIFICATIONS

65" 7000XE Series



ClearTouch

7000XE SERIES INTERACTIVE PANELS

The all-new 7000XE Series with PCAP technology for superior multi-touch control.

65" Panel Specifications

Size	65"
Panel Type	RGB
Aspect Ratio	16:9
Display Area	56" × 31.6"
Resolution	3840(H) × 2160(V)
Pixel Pitch	0.372 × 0.372 mm
Back Light Unit	D-LED
Response Time	6.5 ms
Refreshing Frequency	60Hz
Display Color	1.07B (10 bit)
Brightness (<i>typical</i>)	350 cd/m ²
Contrast Ratio	4000:1
Viewing Angle	178°
Life Time	> 30,000 Hours



4K VIEWING EXPERIENCE



RICH AUDIO EXPERIENCE



INTUITIVE TOUCH EXPERIENCE



COLLABORATION SOFTWARE
WITHOUT SUBSCRIPTION



INTEGRATED DEVICE CASTING



PANEL MANAGEMENT WITH
VIDEO BROADCAST



INTEGRATED MESSAGING AND
ALERT NOTIFICATIONS

PANEL AUDIO

Sound Channel	2.0
Output Power	2 × 10W + 15W

PANEL CONNECTIONS

HDMI Output	1
USB 2.0 (shared across all inputs)	3
USB 3.0 (shared across all inputs)	3
USB-C port (45W PD)	1
Touch Input	2
HDMI Input	3
VGA Input	1
Audio Input	1
RS232 Port	1
Audio Output	1
RJ45 Port with LAN Pass Through to PC	1
SPDIF	1

PANEL INTERACTIVITY

Sensing Type	ITO
Compatibility	Windows10/Windows8/Windows7/ WindowsXP/Linux/MacOSX/ Android/Chrome
Touch Point	10 writing, 20 points touch
Minimum Object Size	2.8 mm
Touch Tool	Finger Capacitive stylus
Response Time	6.5 ms
Accuracy	± 1 mm 90% area
Palm Rejection	Support
Pressure Sensitivity	Support
Simultaneous Writing	Double writing and double pens
Glass Type	Anti-glare 3mm thick glass
Interpolation Resolution	32768(W) x 32768(D)

PANEL OPERATING SYSTEM

System Version	Android 8.0
CPU	Dual core A73 + Dual core A53
GPU	Mali G51×4
RAM	3GB
ROM	16GB

PANEL AMBIENT

Operation Temperature	32°F – 104°F
Operation Humidity	10% – 90%
Storage Temperature	-4°F – 140°F
Storage Humidity	10% – 90%
Altitude	Below 16404.2 ft

POWER

Power Requirements	100-240V ~ 50/60Hz 4.0A
Standby Power	≤0.5W
Overall Power (nominal power)	400W

PHYSICAL SPECIFICATION

Key Location & Number	Right side physical key
Dimension L*W*H	59" × 34" × 3"
Dimension (package) L*W*H	67" × 9" × 21"
Net Weight	87 lbs
Gross Weight	114 lbs
Machine + Wall Mount Thickness	4.5" WIB9060G
Wall-hanging Screw Spec	M8 × 25 mm
VESA	600 × 400 mm

ACCESSORIES

American Standard Power Cord	USB Touch Cable (Type A-B)
HDMI Cable	Remote Control
Pens	AAA Batteries (2)

Quick Start Guide

PC MODULE (OPTIONAL)

Type	Detachable PC module		
Model	CTI-PCMOD-PC45-ST-i5 CTI-PCMOD-PC47-IG-i7 CTI-PCMOD-PC47-VP-i7		
CPU	Intel® Core™ i5 8400 CPU Intel® Core™ i7 8700 CPU		
RAM	DDR4 8GB DDR4 16GB		
SSD	128GB 256GB		
Graphics	Integrated Intel® HD UHD Graphics 630 GT 1030 Independent Graphics		
Chipset	Intel® H310 Intel® Q370		
Sound Card	Integrated high definition Audio stereo		
Networking	10/100/1000MB		
WiFi Version	802.11		
WiFi Frequency	2.4GHz		
WiFi Working Distance	0 ~ 10m		
Bluetooth Version	Bluetooth 2.1; 3.0; 4.0		
Bluetooth Working Frequency	2.4GHz		
Bluetooth Working Distance	0 ~ 10m		
Operating System	Not included	Earphone Output	1
USB 2.0 3.0	6	Microphone Input	1
LAN(RJ45)	1	Display Port Output	1
VGA Output	1	HDMI Output	1

PANEL WARRANTY OPTIONS

Standard	1 year
Registered	3 year
Optional	5 year