

CS100

# Conference Speaker

With Six Array Microphone





**Bluetooth Connectivity** 



Wireless/Wired Charging



**Omnidirectional Microphone** 



**Portable** 

## Main Features

# **BLUETOOTH CONNECTIVITY**

Connect using bluetooth to any compatible device, making meetings more collaborative and efficient.

### WIRELESS/WIRED CHARGING

No more tangled cords or adapters, the CS100 can charge wirelessly with no hassle and hold up to 8 hours of battery life on a single charge.

### **OMNIDIRECTIONAL MICROPHONE**

Move freely and present within a 16ft radius with the CS100's 360-degree omnidirectional microphone.

# **PORTABILITY**

The Conference Speaker's lightweight and compact design makes it easy to transport and carry in-hand between meetings.



PRODUCT	
Model Number	CTS-CS100-BTWC
Model Name	Conference Speaker
SPEAKER	
Sound Channel	1.0
Output Power	1 x 5W
Maximum Sound Pressure Level	85dBSPL @ 0.5m, 1kHz
Distortion	≤1% @ 1W, 1kHz
Signal to Noise Ratio	≥75dB
Frequency Range	150Hz ~ 16kHz
міс	
Microphone Type	6-Element Array, Omni-directional
Voice Pickup Range	5m / 16.4ft (Radius)
Frequency Range	150Hz ~ 7.5kHz
BATTERY	
Battery Capacity	7.4V/2200mAh
Detter Chamin	Wired: 5V/2A
Battery Charging	Wireless: 5W (optional)
Continuous Working Time	8h (Voice communication with the maximum volume)
INPUT/OUTPUT INTERFAC	E
USB Type-C	1 (Audio IN/OUT+Charge 5V/2A)
AUX 3.5mm	1 (Audio IN/OUT)
Button	6
LED Indicator Light	Power/Volume/Button
BLUETOOTH	
Version	BT4.2+EDR
Operating Frequency	2.4GHz
Operating Distance	10m
	Supports audio input and output
USB Dongle	Compatible with Windows, Mac System

GENERAL SPECIFICATION	
Dimensions (Diameter x Height)	120 x 36.5mm / 4.72" x 1.43"
Package Dimension (L x W x H)	225 x 158 x 50mm / 8.85" x 6.22" x 1.96
Net Weight	390.08 g / 0.86 lbs
Gross Weight	693.99 g / 1.53 lbs
INCLUDED ACCESSORIES	
USB Type-C Cable	x1
Audio Cable	x1
USB Dongle (Bluetooth)	x1
ENVIRONMENTAL CONDITIONS	
Operation Temperature	0°C ~ 40°C / 32°F ~ 104°F
Operation Humidity	10% ~ <b>90%RH</b>
Storage Temperature	-20°C <b>~ 60° C</b> / <b>-4°F ~ -76°F</b>
Storage Humidity	10% ~ <b>90%RH</b>
Altitude	Below 5000 meters