

1080P Web Camera



1080 P

USB 2.0 Connectivity & Interface

Main Features

USB 2.0

Full-featured USB 2.0 interface, power, video and audio all-in-one.

EASY INSTALLATION

Equipped with rotary brackets allowing for easy installation on all Clear Touch® panels as well as third party devices. In addition, comes with 1/4 - 20 thread, compatible with most tripods.

LOW LIGHT

Featuring a clear and sharp image even in low light environments.

BUILT-IN MICROPHONE

Built-in microphone array to pick up sound equally from all directions. Unique noise reduction algorithm to accurately capture your voice.







CTS-WC110-UHHD	
1080P Web Camera	
1/2.7", CMOS, effective pixel: 2.07M	
Progressive	
M12	
Focus: <i>f</i> = 2.8mm, FOV: 83°	
0.05 Lux @ (F1.8, AGC ON)	
1/30 ~ 1/1000s	
Auto, indoor, outdoor, one push, manual	
Bracket with damper	
2D, 3D digital noise reduction	
Support	
Windows® 7 (1080p and under only), Windows 8.1, Windows 10 or higher macOS™ 10.10 or higher Google™ Chromebook™ version 29.0.1547.70 or higher Linux	
2.4 GHz Intel® Core 2 Duo processor or higher 2 GB RAM or more USB 2.0 port	
H.265 / H.264 / MJPEG	
1080P at 30fps/25fps 960x540p at 30fps/25fps 720p at 30fps/25fps 640x360p at 30fps/25fps	
UVC 1.0 ~ UVC 1.5	
1 x USB 2.0: Type A	
5V (USB power supply)	
270mA	
14°F ~ 104°F	
-40°F ~ 140°F	
1.4W	
4.65" L x 1.47" W x 1.21" H (not including bracket)	
3.3 oz. (not including bracket)	
3.3 oz. (not including bracket) 30000h	
	1/2.7", CMOS, effective pixel: 2.07M Progressive M12 Focus: f = 2.8mm, FOV: 83° 0.05 Lux @ (F1.8, AGC ON) 1/30 ~ 1/1000s Auto, indoor, outdoor, one push, manual Bracket with damper 2D, 3D digital noise reduction Support Windows® 7 (1080p and under only), Windows 8.1, Windows 10 or higher Google™ Chromebook™ version 29.0.1547.70 or higher Linux 2.4 GHz Intel® Core 2 Duo processor or higher 2 GB RAM or more USB 2.0 port H.265 / H.264 / MJPEG 1080P at 30fps/25fps 960x540p at 30fps/25fps 720p at 30fps/25fps 960x540p at 30fps/25fps UVC 1.0 ~ UVC 1.5 1x USB 2.0: Type A 5V (USB power supply) 270mA 14°F ~ 104°F -40°F ~ 140°F 1.4W

