

## WebSensor with PoE - remote thermometer with Ethernet interface

code: T4611



Ambient temperature t-line Web sensor for Pt1000 sensor with Power over Ethernet feature. Remote alarm.  
PoE Web Sensor for external Pt1000 temperature probe. Power over Ethernet feature according IEEE 802.3af is supported.

### Processing and analysis of measured data:

- online in [COMET Cloud](#)
- [COMET Database](#) software
- [integration into 3-party systems](#)

### Technical data

|                                            |                                                       |
|--------------------------------------------|-------------------------------------------------------|
| TEMPERATURE SENSOR - external probe Pt1000 |                                                       |
| Measuring range                            | -200 to +600 °C                                       |
| Accuracy                                   | ±0.2°C                                                |
| Resolution                                 | 0.1 °C                                                |
| GENERAL TECHNICAL DATA                     |                                                       |
| Operating temperature                      | -30 to +80 °C                                         |
| Channels                                   | 1x external temperature probe                         |
| Output                                     | Ethernet                                              |
| Measuring interval                         | 2 s                                                   |
| Available temperature units                | degrees Celsius, degrees Fahrenheit                   |
| Communication protocol                     | WWW, ModbusTCP, SNMPv1, SOAP, XML                     |
| Alarm protocols                            | E-mail, SNMP Trap, Syslog                             |
| Power                                      | Power over Ethernet according to IEEE 802.3af or 5Vdc |
| Protection class                           | IP30                                                  |
| Dimensions                                 | 136 x 149 x 45 mm                                     |
| Weight                                     | approx. 145 g                                         |
| Warranty                                   | 3 years                                               |