

# AC SMARTSEAL™

## QUICK SHOT



### Leak Stop for HVAC and Refrigeration

AC SMARTSEAL Quick Shot is a leak stop which represents the evolution of AC SMARTSEAL, with a higher effectiveness that has allowed the reduction of the dosage to be used within the unit. Specifically designed to permanently repair leaks both in rubber and metal parts of a system, AC SMARTSEAL Quick Shot guarantees a total seal for leaks. Its mechanical action works within the unit, without any kind of chemical reaction. AC SMARTSEAL Quick Shot is polymer free: it is not reactive to oxygen and moisture and is suitable for any type of lubricant and refrigerant gas.

AC SMARTSEAL Quick Shot has been widely tested on many models of compressors to ensure the normal operation. It has been shown that there is a reduction of the compressor noise. Similar evidence was found in the interaction with the recovery station that is neither clogged nor damaged. AC SMARTSEAL Quick Shot particles are similar to the lubricant and refrigerant gases. AC SMARTSEAL Quick Shot does not stop inside the drier filter and does not accumulate in the expansion valve.

Instructions for the use of Easy Inject Kit in AC/R systems:

1. Turn the A/C system on. If the unit is a heat pump, be sure it is set on cooling mode. Connect the cartridge to Easy Inject and fully inject sealant in it.
2. Connect Easy Inject to the low-pressure service port of A/C system. Connect a charging hose to a refrigerant cylinder.
3. Briefly open the cylinder valve to purge air out of the charging hose. Quickly tighten the charging hose fitting to Easy Inject. Inject refrigerant through Easy Inject and push sealant into the A/C system.
4. Run A/C system for 30 minutes to allow the product to fully circulate.

