





Versatile and Brilliant for any Projection Demands

Featuring 5500 lumens of brightness, a 10000:1 contrast ratio, DLP® dark chip 3 and BrilliantColor™ technologies, with Full 3D capability. The Vivitek D967 digital projector has impressive color reproduction and delivers amazing performance. With a built-in speaker, an assortment of connectivity options, including 3D sync, and RJ45/RS232, the D967 integrates effortlessly into almost any situation where a powerful projector is needed.

Features

- High 5500 lumens of brightness with a 10000:1 contrast ratio
- DLP® dark chip 3 and BrilliantColor™ technologies for sharp and detailed image quality
- VividWheel III for improved color reproduction and automatic gain control
- Full 3D capability
- Connectivity options include: HDMI V1.4 (x2), Display Port, VGA-in (x2), VGA out, Composite video, S-Video
- RJ45/RS-232c for integration and system administration
- 12V trigger for simple screen/projector automation
- Top-loading, sliding cover for quick and easy lamp replacement
- Keypad lock prevents accidental system adjustments













205 Westwood Ave, Long Branch, NJ 07740 Phone: 866-94 BOARDS (26273) / (732)-222-1511 Fax: (732)-222-7088 | E-mail: sales@touchboards.com

Specifications	
Brightness (Typical)	5500 ANSI Lumens
Native Resolution	XGA (1024 x 768)
Max. Resolution	WUXGA (1920 x 1200)
Contrast Ratio	10000:1 (Full On/Off)
Lamp Life and Type	2500/3500/4000 Hours (Normal/Eco/Dynamic Eco), 310W
Lamp Part #	5811118436-SVV
Display Type	Single 0.7" DLP® Technology by Texas Instruments
Throw Ratio (±3%)	1.8 to 2.1:1 (Distance/Width)
Image Size (Diagonal)	23.4" to 300" (0.6 to 7.6 m)
Projection Distance	4.92' to 32.8' (1.5 to 10 m)
Projection Lens	F=2.6-2.81, f=26.01- 29.84 mm
Zoom Ratio	1.15:1 Manual Zoom/Focus
Aspect Ratio	4:3 Native, 16:9 Compatible
Offset	124%
Keystone Correction	± 40° Vertical (± 40 steps)
Color Spectrum	16.7 Million
Horizontal Scan Rate	15, 30 to 90 KHz
Vertical Scan Rate	43 to 85 Hz
Speaker	5W Mono
Remote Control	Fully Featured IR Remote with Laser Pointer
Projection Method	Table Top or Ceiling Mount (Front or Rear)
Uniformity	85%
Computer Compatibility	WUXGA, UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible
Video Compatibility	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC/NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM
I/O Connection Ports	HDMI v1.4 (x2), Display Port, VGA-In (x2), Video, S-Video, VGA-Out, RCA Stereo-In, Mini-Jack Audio-In, Mini-Jack Audio-Out, RJ45, 12V Trigger,RS-232c, 3D Sync, USB (Service)
Security	Kensington® Lock Port, Security Bar
Weight	8.3lbs (3.76kg)
Dimensions (W x H x D)	13.1" x 4.4" x 10" (335 x 113 x 255 mm)
Noise Level	35dB/35dB (Eco/Normal)
Power	Supply: AC 100-240V, 50/60Hz Consumption: 300W/370W (Eco/Normal) <0.5W (Standby Mode)
Operating Temperature	41 to 95°F (5 to 35°C)
Warranty	3-Year Limited Parts/Labor, 1-Year Lamp
Standard Accessories	AC Power Cord, VGA Cable, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, User Manual (CD), Warranty Card
UPC	814964 338952
Part of the second seco	