

# GENERAL®

## Ruggedized Video Inspection System

Ideal for inspecting **Hard-To-Reach** or **Hard-To-See** Areas of your Vehicle.  
Design is ruggedized for automotive use.

### Features & Benefits:

- One button starts/stops logging without a PC
- Includes long (1 m/39 in.), thin (9mm/0.35-in. diameter) camera-tipped probe for reaching deep into tight spaces. Longer, thinner probes and extensions of up to 3m are available.
- Included probe and all optional probes are oil, water and dust-proof to IP67 standard. The SEEKER™280's wand-type grip and monitor are IP54 splash-proof.
- Unit is drop-resistant to 1m height and comes in protective hard case
- Pays for itself quickly: Avoid the cost and trouble of tearing down engines
- One-handed operation frees your other hand to use tools
- Powered by "AA" batteries
- Big, bright color LCD shows crystal-clear real-time video
- Included probe is in focus from 1 in. to infinity
- Two adjustable LEDs illuminate dark areas
- Invert what you see 180° to read labels right-side up and ZOOM video up to 200% to show details
- AV Out jack sends video to a larger screen
- Includes four useful probe tip accessories (thread protector, magnetic pickup, pickup hook and 45° mirror)
- Three-year limited warranty

### Includes:

Video Camera Scope with Wand-type Grip, 1 m (39 in.) Long, 9mm (0.35 in.) Diameter Flexible-Obedient Probe, 2.4 in. Color LCD Monitor, 4 Probe Tip Accessories (Thread Protector, Magnetic Pickup, Pickup Hook, 45° Mirror), 4 "AA" Batteries, Custom Hard Case, User's Manual and 3 Year Warranty



Long, thin probe reaches deep into tight spaces



Perfect for driveway mechanics

No. DCS280

# GENERAL®

General Tools & Instruments

80 White Street, New York, NY 10013-3567

TEL: 212. 431. 6100 TOLL FREE: 800. 697. 8665

sales@generaltools.com www.generaltools.com

DCS280SS Printed in USA 12/11

**GENERAL<sup>®</sup>**

## Ruggedized Video Inspection System

Ideal for inspecting Hard-To-Reach or Hard-To-See Areas of your Vehicle.  
Design is ruggedized for automotive use.

### Specifications:

**Display Size/Type:**

2.4 in. diagonal TFT color LCD

**Display Resolution:** 320 x 240 pixels

**Monitor Controls:**

180° flip, 1 to 2X zoom in 0.2 steps,  
brightness + and -

**Probe Diameter & Type:**

9mm (0.35 in.) flexible-obedient

**Probe Length:** 1m (39 in.)

**Probe Field of View:** 60°

**Probe Depth of Field:** 1 in. to infinity ∞

**Camera Light Source:**

2 adjustable-brightness white LEDs

**Impact Resistance:** To height of 1m (39 in.)

**Water, Dust, Splash Resistance Levels:**

Camera-tipped probe designed to meet IP67;  
Grip and monitor designed to meet IP54

**Operating Temperature/Humidity:**

32° to 113°F (0° to 45°C) @ 5 to 95% RH

**Dimensions of Grip:**

10 x 3.6 x 2.3 in. (254 x 91 x 58mm)

**Weight of Grip:** 1 lb. (454g)

**Dimensions of Case:**

15 x 11 x 3.5 in. (381 x 279 x 89mm)

**Weight of Case and Contents:** 4 lb. (1.8 kg)

**Power Source:** 4 "AA" batteries (included)



Long, thin probe reaches deep into tight spaces



Avoid the time and hassle of engine teardowns



Save 90% of the cost of an engine teardown each time



No. DCS280

**GENERAL<sup>®</sup>**

General Tools & Instruments

80 White Street, New York, NY 10013-3567

TEL: 212. 431. 6100 TOLL FREE: 800. 697. 8665

sales@generaltools.com www.generaltools.com

DCS280SS Printed in USA 12/11