DV-MFSW-94

9x4 Presentation Matrix Switcher







Connect with Confidence

The DV-MFSW-94 is a hybrid matrix switcher that allows both analog and digital video sources to be reliably routed to as many as four digital displays. The compact, 3RU unit will accept up to 9 sources and 4 HDMI outputs.

The FSR Digital Video series was designed to reduce the integration challenges that have become a painful norm in deployment of digital display systems. The connections between sources and displays are rife with known and unknown pitfalls that need to be addressed by system designers. Cable length is critical as is the ability to accept a wide variety of signal types and resolutions and then reliably display them at a common endpoint.

When you are compelled to shoehorn massive amounts of technology into small spaces, you need solutions that can do the job and fit the space. Few new installations have dedicated wiring closets, so it is common for systems to be housed inside the furniture within the presentation room.

APPLICATIONS

- Video Wall System
- Large LED Sian Board
- Medical Imaging Equipment
- TV Broadcast Station
- Auditorium
- Conference Room
- Church Video System

205 Westwood Ave, Long Branch, NJ 07740 Phone: 866-94 BOARDS (26273) / (732)-222-1511 Fax: (732)-222-7088 | E-mail: sales@touchboards.com






Specifications are subject to change without notice.

FEATURES

- HDMI V1.3
- HDCP V2.1
- Input Diversity VGA, HDMI, DVI, YUV, S-video or Composite video
- Scaled Output Digital video perfectly scaled for each display device
- True Independent Audio and Video Matrixing
- 3 Fiber or Cat-x inputs Use distant sources without extender clutter
- Additional 5th Audio Output Sound systems can be supplied with Analog Audio from any source
- IP and RS232 Controllable
- · Requires only 3U of rack space



FSR Inc.

244 Bergen Boulevard, Woodland Park, NJ 07424 Phone: 973.785.4347 · Fax: 973.785.4207

Order Desk: 1-800-332-FSR1

Web: www.fsrinc.com · E-mail: sales@fsrinc.com

SPECIFICATIONS

Inputs	Port Type	Setup	Signal Option
Digital Video x 4	HDMI F	Select	DVI
			HDMI
Analog Video x 2	DB-15	- Select	RGB — up to UXGA
			YUV —up to 1080p
	S-Video		YC S-Video
	1 x RCA		CV Composite
HDMI CAT-x Extender X 3 DV-HXT-1	Fiber Optic LC x 2	Select	DVI/HDMI
	CAT 6		
Audio Inputs x 11	uts x 11 4 x 3.5mm TRS Select	Coloot	Analog Stereo
	4 x HDMI	Select	HDMI Audio
	2 x Phoenix	n/a	Balanced Audio
	2 x RCA	n/a	L&R Unbalanced Audio
HDMI CAT-x Extender X 3 DV-HXT-1	3 x Fiber or CAT 6	Auto	HDMI Audio
Outputs	Port Type	Setup	Signal Option
Digital Video x 4	HDMI F	Select	DVI
			HDMI
Audio Outputs x 5	4 x RCA/Toslink	n/a	SPDiF
	1 x RCA (L&R)	Select	L&R unbalanced Audio
Power	DC-12V, 6.6A, 25 Watt / 35 Watt		
Dimensions (WxLxH)	17.125in (435mm) x 10.629in (270mm) x 3.464in (88mm) (3U)		
Weight	17.5 lb.		



FSR Inc.



Phone: 866-94 BOARDS (26273) / (732)-222-1511 Fax: (732)-222-7088 | E-mail: sales@touchboards.com