



Acceleration	Peak Value: 0.1-400m/s ² or 0.3-1312ft/m/s	Frequency Range: 10Hz-1KHz Frequency Range: 10Hz-10KHz
Velocity(RMS)	RMS: 0.1-400 (mm/s) or 0.004 -16.0 inch/s	Frequency Range: 10Hz-1KHz
Displacement	peak to peak: 0.001-4.0mm or 0.04-160mil 10Hz-1KHz	Frequency Range: 10Hz-500Hz
RPM Frequency	5-100,000 r/min	
Frequency	0.1 - 10KHz	
Accuracy	<5%	
Operating Temp	0-45°C	
Power	4-AAA Batteries	
Dimensions	161 x 69 x 32mm	
Weight	10.5 oz.	

Features:

- Quick accurate analysis for checking balance and alignment of a rotating object.
- Large LCD display
- Statistics: Mean, Max, MIN, No. of Measurements and Std deviation
- Inch/Metric Conversion with the push of a button
- Max Hold Function
- Regulated Output(AC output 2.0v peak full scale)

DVM Includes:

- 1-Powerful Magnet
- 1-Accelerometer
- 1-Stinger Probe (cone)
- 1-Stinger Probe (Ball)
- Operation Manual
- Carry Case

Multi-functional meter is capable of measuring Velocity, Acceleration, Displacement and RPM Frequency.

DVM-1000 Digital Vibration Tester