



These adapters are designed to join two male RG6, RG6 Quad Shield, RG59, RG59 Quad Shield CATV F connectors. These adapters also feature the following:

- For performance up to 3.0 GHz
- Gold-plated contacts for maximum performance
- For use with male RG6, RG6 Quad Shield, RG59, RG59 Quad Shield CATV F connectors

| SPECIFICATIONS      |                                 |
|---------------------|---------------------------------|
| CONNECTOR TYPE      | F Female Splice Adapter         |
| STANDARDS           | IEC 60169-24                    |
| TEMPERATURE RANGE   | -40~+85°C                       |
| VIBRATION           | 100 m/s <sup>2</sup> (10~500Hz) |
| IMPEDENCE           | 75 Ω                            |
| FREQUENCY RANGE     | DC~1GHz                         |
| WORKING VOLTAGE     | 170V                            |
| WITHSTAND VOLTAGE   | 500V                            |
| CENTER CONTACT RES. | ≤ 10 mΩ                         |
| OUTER CONTACT RES.  | ≤ 5 mΩ                          |
| INSULATION RES.     | ≥ 1000 MΩ                       |
| RETURN LOSS         | ≥ 25dB                          |
| INSERTION LOSS      | ≤ 0.8 dB                        |
| WEIGHT              | 0.02 lb (9.08 g)                |
| UPC #               | 810053351703                    |

