



SPECIFICATIONS:

Material Properties:

- Dissipative Polyvinylchloride (PVC)
- Material Thickness: 0.012" (1S) front & back
- Material Tolerance (thickness): +/-10%
- Material Finish: Matte
- 1" header imprinted with ESD Protective Symbol
- 2-1/2" x 3-1/2" Badge Holder display
- 3-1/2" x 5-13/16" OD

Electrical Properties:

• Rs: 1 x 10⁶ to < 1 x 10¹¹ ohms per ANSI/ESD STM11.11

ltem	Description	
<u>07474</u>	ESD Pocket Protector	

"It should be understood that any object, item, material or person could be a source of static electricity in the work environment. Removal of unnecessary nonconductors, replacing nonconductive materials with dissipative or conductive materials and grounding all conductors are the principle methods of controlling static electricity in the workplace, regardless of the activity." [ESD Handbook ESD TR20.20 section 2.4 Sources of Static Electricity]



Specifications and procedures are subject to change without notice United States of Americ

Dimensional tolerances are +/- 1/16" unless specified	ESD POCKET PROTECTOR		
	DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEBSITE: <u>Desco.com</u> PHONE (909) 627-8178 FAX (909) 627-7449 DESCO EAST: ONE COLGATE, CANTON, MA 02021-1407	DRAWING NUMBER	DATE February
	PHONE (781) 821-8370 FAX (781) 575-0172	07474	2014

© 2014 DESCO INDUSTRIES INC. Employee Owned