

Grounding & Cleaning

If the material is used on top of an already properly grounded surface, grounding hardware may not be necessary. Where no properly grounded surface is available, grounding hardware is required to provide a path-to-ground. Rtg compliance verification measurements must be made as outlined in ESD TR53 with a surface resistance meter.

See Tech Bulletin <u>TB-7000</u> for Reztore[®] Surface & Mat Cleaner Application Instructions.

RoHS 3, REACH, and Conflict Minerals Statement
See the Desco Industries RoHS 3, REACH, and Conflict Minerals Statement:
Descoindustries.com/ROHS.aspx

See the Desco Limited Warranty:

Desco.Descoindustries.com/Limited-Warranty.aspx

See the Desco Disclaimer:

Desco.Descoindustries.com/Disclaimer.aspx

Statfree S Plus™ Dissipative Homogeneous Vinyl

Specifications

ANSI/ESD S20.20

Standard Document

Meets Requirements of:

Flooring

Electrical Properties

Typical Values

Test Procedures/Method

Rtt Resistance: <1 x 10⁹ ohms Rtq Resistance: <1 x 10⁹ ohms ANSI/ESD STM7.1 and ESD TR53 ANSI/ESD STM7.1 and ESD TR53

Physical Properties

Construction: Vinyl/Nitrile Floor Runner

Thickness: 0.375" Color:** Grey

Texture:** Non-directional, heavy embossed, soil and abrasion resistant

Weight: $0.65 \, \text{lbs/ft}^2 \, (0.317 \, \text{g/cm}^2)$

Tolerances:

Width +/- 0.250"

Length +/- 0.250" every 1 linear foot of running material.

Matting materials have a tendency to shrink slightly when first unrolled. In applications where length is critical, allow the material to relax for at least 4 hours before cutting to size. Always trim with a sharp knife or razor blade.

STATFREE S PLUS™ FLOOR MAT, VINYL, HOMOGENEOUS,

**Color and texture may vary between lots and mills

For Sizes and Item Numbers, Click Here





Specifications and procedures subject to change without notice

DESCO

DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: Desco.com

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407 PHONE (781) 821-8370 FAX (781) 575-0172

PHONE (909) 627-8178 FAX (909) 627-7449

ANTI-FATIGUE, .375" (9.5MM)

MATERIAL STATFREE S Plus DRAWING PM-120 **DATE:** February 2019