



- A. Fixed light gray ABS cap with slotted opening to allow size adjustment.
- B. 300 series stainless steel backplate forms channel to hold up to 10 links of band allowing size adjustment.
- C. Machined nickel plated steel stud. Fits Desco's MagSnap® coil cords. Coil cord disengages from from snap with 1-5 lbs. of perpendicular force.
- D. Metal expansion wrist strap. Inside links are constructed of 300 series stainless steel. Width of links is 0.630". Minimum Circumference: 5.75" and Maximum Circumference: 13".

- E. 0.002" polyphenylsulfone sheet is laminated to each link. Provides >5,000 volt RMS insulation per ASTM D149. Scratch resistant. Color white.
- F. Size is adjusted by sliding 1 to 10 links of the band into the backplate "C" channel.
- G. 300 series stainless steel clip for electrical contact between stud and backplate.
- H. Underwriters Laboratory listing 90P1C.

Meets ANSI/ESD S20.20 and Wrist Strap standard ANSI/ESD S1.1.

**Standard items that include MagSnap® Metal Expansion Wristbands**

Item	Description	Cord Style	Accessories
<a href="#">09210</a>	Wristband	N/A	None
<a href="#">09211</a>	Wrist Strap	<a href="#">6 Foot Magsnap® Coil Cord</a>	Alligator Clip
<a href="#">09212</a>	Wrist Strap	<a href="#">10 Foot Magsnap® Coil Cord</a>	Alligator Clip

Meets ANSI/ESD S20.20 wristband resistance interior < 100 kilohms (< 1 x 10<sup>5</sup> ohms) per ANSI/ESD S1.1.  
 Meets ANSI/ESD S20.20 wristband resistance exterior >10 megohms (> 1 x 10<sup>7</sup> ohms) per ANSI/ESD S1.1.

Unless otherwise noted, tolerance ± 10%

Specifications and procedures subject to change without notice.



Made in the United States of America

**JEWEL MAGSNAP® WHITE METAL ADJUSTABLE WRIST STRAPS**



**DESCO WEST:** 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: [Desco.com](http://Desco.com)  
 PHONE (909) 627-8178  
**DESCO EAST:** ONE COLGATE WAY, CANTON, MA 02021-1407  
 PHONE (781) 821-8370

**DRAWING NUMBER**  
09210

**DATE:**  
September  
2014