



STATFREE® ESD ULTRA CLEAR BAG

Meets the required limits of ANSI/ESD S20.20, Packaging standard ANSI/ESD S541, and Static Control Bag standard ANSI/ESD S11.4 Level 5.

Specifications:

Electrical Properties

Electrical Properties	Typical Value
Surface Resistance: (Interior and Exterior)	1×10^4 to $< 1 \times 10^{11}$ ohms
Charge Generation: Teflon	-0.10 (nC/in ²)
Quartz	+0.10 (nC/in ²)

Test Procedures/Method

per ANSI/ESD STM11.11
Modified Incline Plane
Modified Incline Plane

Physical Properties:

Thickness	Nominal 3.5mil (.09mm) ±10%	MIL-STD-3010, 1003
Width (Inside Dimensions)	Nominal -0" / + 1/4"	
Length (Inside Dimensions)	Nominal +/- 1/8", Offset 0" to 1/4"	
Light Transmission	>90 (%)	STM D-1003
Heat Seal	>8 (lbs/in)	375°F, .75 sec 60 psi
Tensile Strength	>5,300 (MD/TD, psi)	ASTM D-882
Puncture Resistance	>14 lbs	MIL-STD-3010, 2065
Silicone	Not detected	FTIR
MVTR	0.35 (grams / 100 in ² / 24 hrs)	ASTM F-1249

Chemical Properties

Polycarbonate compatible: Contains no Amines, Amides, or N-Octanoic Acid.

Bag is free of amines, N-octanoic acid, silicones and heavy metals.

ANSI/ESD S541 section 6.1 Inside an EPA

"Packaging used within an EPA (that satisfies the minimum requirements of ANSI/ESD S20.20) shall be:

- Low charge generation
- Dissipative or conductive materials for intimate contact"

RoHS, REACH and Conflict Minerals, Statement

See the Desco Industries RoHS, REACH, and Conflict Minerals Statement:
https://desco.descoindustries.com/pdf/Regulatory_Statements_Desco_Statshield_Bags.pdf

See the Desco Limited Warranty:


[Desco.DescoIndustries.com/Limited-Warranty.aspx](https://descoindustries.com/Limited-Warranty.aspx)

Statshield® and Statfree® are Registered Trademarks of Desco Industries Inc.
See Bag Selection Chart Click [HERE](#).


Specifications and procedures subject to change without notice.



Made in the United States of America



** Bags are printed (hot stamped or thermal transferred) with an ESD protective symbol and a lot code for traceability. **



Mixed Unsortable Plastic Scrap

Mixed unsortable plastic scrap shall contain assorted plastics of multiple grades that are co-extruded, bonded or laminated together which are unsortable into individual grades

Desco's bags are recyclable

Statshield® bags are packaged 100 per package in an oversized shielding bag.
See Shielding Bag Storage at [TB-7057](#).

STATFREE® ESD ULTRA CLEAR BAG WITH ZIPPER, 3.5MIL (.09mm)

DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: [Desco.com](https://desco.com)
PHONE (909) 627-8178

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407
PHONE (781) 821-8370

DRAWING NUMBER
13880

DATE:
September 2021

DESCO