







Key Specifications

Lumens™

No.	Model	DC120	DC125	DC170
1	Photo			
2	Optical Zoom	NA	NA	2x Sensor Zoom
3	Mechanical Zoom	7x	8x	9x
4	Digital Zoom	8x	8x	12x
5	Output Resolution	XGA, SXGA, WXGA, UXGA	XGA, SXGA, 720p, 1080p, UXGA, QXGA	XGA, SXGA, WXGA, 1080p
6	Frames Rate	30 fps (max)	30 fps	30 fps
7	Shooting Area	420 x 315 mm (16.5" x 12.4")	420 x 315 mm (16.5" x 12.4")	442 x 331 mm (17.4" x 13")
8	Lamp	LED x 1	LED x 1	LED x 2
9	Power	USB bus power	USB bus power	Built-in Power Supply, 100-240VAC
10	Input	NA	NA	VGA
11	Output	USB	USB	VGA, HDMI, USB, C-Video
12	Built-in Microphone	Yes	Yes	Yes
13	Memory Slot	NA	NA	SD Card
14	Built in Memory	NA	NA	240 pictures
15	Image Rotation	0°, 180°	0°, 180°, Flip, Mirror	0°, 180°, Flip, Mirror
16	Standalone AV Recording	Audio/Video (by software)	Audio/Video (by software)	Audio/Video Recording
17	Projector Mode	NA	NA	DLP/LCD mode
18	Free Software	Ladibug (MAC, Win 8, 7, Vista, XP)	Ladibug (MAC, Win 8, 7, Vista, XP)	Ladibug (MAC, Win 8, 7, Vista, XP)

No.	Model	DC192	DC265	3D101
1	Photo			
2	Optical Zoom	16x	6x	NA
3	Mechanical Zoom	10x	14x	8x
4	Digital Zoom	12x	6x	8x
5	Output Resolution	XGA, SXGA, WXGA, 1080p	XGA, SXGA, UXGA, HD 720p, 1080p	XGA, SXGA, WXGA, UXGA
6	Frames Rate	30 fps	30 fps (max)	30 fps (max)
7	Shooting Area	400 x 300 mm (15.7" x 11.8")	400 x 300 mm (15.8" x 11.8")	542 x 407 mm (21.3" x 16")
8	Lamp	LED lamp x2	Cold cathode x2	NA
9	Power	Built-in Power Supply, 100-240VAC	Built-in Power Supply, 100-240VAC	USB bus power
10	Input	VGA, HDMI	VGA	NA
11	Output	VGA, HDMI, USB, C-Video	VGAx2, HDMI, USB, C-Video	USB
12	Built-in Microphone	Yes	Yes	Yes
13	Memory Slot	USB flash drive	SD Card	NA
14	Built in Memory	240 pictures	240 pictures	NA
15	Image Rotation	0°, 180°, Flip, Mirror	0°, 90°, 180°, 270°	0°, 180°
16	Standalone AV Recording	Audio/Video Recording	Audio/Video Recording	Audio/Video (by software)
17	Projector Mode	DLP/LCD mode	DLP/LCD mode	NA
18	Free Software	Ladibug (MAC, Win 8, 7, Vista, XP)	Ladibug (MAC, Win 8, 7, Vista, XP)	3D: 3D Hub 2D: Ladibug

* Features and Specifications are subject to change without notice.

Key Specifications

No.	Model	PS750	PS760	CL510
1	Photo			
2	Optical Zoom	16x	20x	25x
3	Digital Zoom	6x	5x	5x
4	Output Resolution	XGA, SXGA, 720p	XGA, SXGA, WXGA, UXGA, 1080p	XGA, SXGA, WXGA, UXGA, 1080p
5	Frames Rate	30 fps(max)	30 fps (max)	30 fps (max)
6	Shooting Area	400 x 300 mm (15.7" x 11.8")	464 x 342 mm (18" x 13.7")	Distance at 2m (78.7") Max: 1200 x 900 mm (47.2" x 35.4") Min: 48 x 36 mm (1.9" x 1.4")
7	Lamp	LED x2, A4 size LED backlight	LED x2, A4 size LED backlight	Laser indicator
8	Power	External, 12V DC Adapter (100-240VAC)	External, 12V DC Adapter (100-240VAC)	1. External, 12V DC Adapter (100-240VAC) 2. PoE(Power over Ethernet)
9	Input	VGA(x2), C-Video	VGA(x2), C-Video	NA
10	Output	VGA(x2), HDMI, USB, C-Video	VGA(x2), HDMI, USB, Ethernet, C-Video	VGA, DVI, USB, Ethernet
11	Control	RS-232, USB	RS-232, USB, Ethernet	RS-232, USB, Ethernet
12	Built-in Microphone	Yes	Yes	NA
13	Built-in Speaker	NA	Yes	NA
14	Memory Slot	SD Card	USB flash drive	USB flash drive
15	Built in Memory	240 pictures	120 pictures	120 pictures
16	Image Rotation	0°, 90°, 180°, 270°	0°, 90°, 180°, 270°	0°, 90°, 180°, 270°
17	Standalone AV Recording	Audio/Video Recording	Audio/Video Recording	Video Recording
18	Projector Mode	DLP/LCD mode	DLP/LCD mode	DLP/LCD mode
19	Free Software	Podium View (MAC, Win 8, 7, Vista, XP)	Podium View (MAC, Win 8, 7, Vista, XP)	Podium View (MAC, Win 8, 7, Vista, XP)

* Features and Specifications are subject to change without notice.

LumensTM
Brilliance by Design

www.MyLumens.com



Touchboards

205 Westwood Ave, Long Branch, NJ 07740
Phone: 866-94 BOARDS (26273) / (732)-222-1511
Fax: (732)-222-7088 | E-mail: sales@touchboards.com

Image is so real like a crystal.

