Moisture Meter Model CA847



CE

The Moisture Meter Model CA847 is designed to measure the level of moisture in wood and construction materials such as plaster and roughcast, etc. The measurement principle is as follows: an electric current is passed through the two electrodes in order to measure the impedance variation due to the moisture in the material. The instrument immediately translates the measurement into a humidity percentage. For wood, the instrument gives a direct reading of the level of moisture in the wood, expressed as a percentage of H₂O between 6% and 100%. For other construction materials, the instrument determines the wood moisture equivalent (WME).

Features

- · Easy one-hand operation
- Measurement range: to 100% of H₂O
- Two 20-LED display scales: from 6 to 23% and 24 to 100%
- Replaceable electrodes
- Power ON/OFF automatically activated when protective cover is removed/installed
- · Lightweight and compact
- · Removable protective sensor cover
- · Includes rugged, shockproof, protective, dirt resistant holster

Applications

- · Measure moisture in wood products
- · Plastic, sheetrock and concrete curing

Specifications

MODEL	CA847
MEASUREMENTS — % H ₂ O	
Measurement Range	6 to 100%
Display Resolution	1%
Accuracy	±2 lights
MECHANICAL	
Display	20 LEDs on 2 scales
Operating Temperature	32° to 122°F (0° to 50°C), <80% RH
Storage Temperature	-4° to 140°F (-20° to 60°C), 0 to 80% RH without battery
Power Source	9V Alkaline battery
Low Battery Indication	LED lights up
Dimensions	7.68 x 2.38 x 1.5" (195 x 60.5 x 38mm)
Weight	Approx. 5.6 oz (160g) including battery



Measure the moisture levels in a variety of construction materials with the Moisture Meter Model CA847.



Protective cover also acts as power switch remove cover to turn instrument on; replace cover to turn instrument off.

Construction



- 1. Measurement probes
- 2. ON/OFF switch
- 3. ON light
- 4. Low battery indicator
- 5. Graduated scale showing percentage of moisture in wood
- 6. Protective cover
- 7. Lamp indicating level >23%
- 8. Test button
- 9. 20 moisture level indicator lamps
- 10. Colored barchart

ORDERING INFORMATION

CATALOG NO.

Includes 9V Alkaline battery, rugged, shockproof, protective, dirt resistant gray holster and user manual



Contact Us

United States & Canada:

Chauvin Arnoux®, Inc. d.b.a. AEMC® Instruments 200 Foxborough Blvd. Foxborough, MA 02035 USA (508) 698-2115 • Fax (508) 698-2118 www.aemc.com

Customer Support - for placing an order, obtaining price & delivery:

customerservice@aemc.com

Sales Department – for general sales information:

sales@aemc.com

Repair and Calibration Service - for information on repair & calibration, obtaining a user manual:

repair@aemc.com

Technical and Product Application Support –for technical and application support:

techinfo@aemc.com

Webmaster - for information regarding www.aemc.com:

webmaster@aemc.com

South America, Central America, Mexico, Caribbean, Australia & New Zealand:

Chauvin Arnoux®. Inc. d.b.a. AEMC® Instruments 15 Faraday Drive Dover, NH 03820 USA (978) 526-7667 • Fax (978) 526-7605 export@aemc.com www.aemc.com

All other countries:

Chauvin Arnoux SCA 190, rue Championnet 75876 Paris Cedex 18. France 33 1 44 85 45 28 • Fax 33 1 46 27 73 89 info@chauvin-arnoux.com www.chauvin-arnoux.com

