

Data Sheet



TR200

Temperature / RH Data Logger with Digital Display

Amprobe's Model TR200 takes both temperature and relative humidity readings in one compact size unit. Use the included Amprobe software for recording measurements to your personal computer. Set up these parameters for recording: Sample interval timing, Start/Stop, Date and Time, HI/LO Alarm Threshold, Unit Selection, and number of Memory points.

- Instrument for indoor air quality monitoring
- Wall mountable
- Digital display
- Air Temperature displays in Celsius or Fahrenheit
- Temperature / RH in one model
- Offers visible LEDs warnings to monitor IAQ condition
- Small size design with RS232 interface
- Memory points selection : 1000, 2000, 4000, 8000, 12000, 16000
- Includes RS232 Cable, Download Suite Software CD, User Manual and Battery

No hassle warranty

No waiting.

No shipping charges.



Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSLP limit)





TR200 Temperature / RH Data Logger with Digital Display

Data Sheet

Specifications

General

Display	3 3/4 digit liquid crystal display (LCD) with a maximum reading of 1999
Sampling points	1K / 2K / 4K / 8K / 12K / 16K
Resolution	Temperature 0.1°C / 0.1°F RH Resolution 0.1%
LED	Red: Hi, LO Alarm; Yellow: Record
Low battery indication	The "Batt" is displayed when the battery voltage drops below the operating level
Auto power off	approx 10 minutes
Operating environment	-10°C to 60°C (14°F to 140°F), 0 to 100 %RH
Storage temperature	-40°C to 85°C (-40°F to 185°F), 0 to 100 %RH
Measurement ranges	Temperature Internal sensor -40°C to 85°C (-40°F to 185°F) External probe -40°C to 100°C (-40°F to 212°F) Relative Humidity 0.0 to 99.9%
Accuracy	Temperature ±0.6°C (-20°C to 50°C); ±1.2°C for all others ±1°F (-4°F to 122°F); ±1.2°F for all others Relative Humidity ±3% at 25°C / 77°F; 5% for all others
Sensor	Silicon photodiode and filter
Altitude	2000m, indoor operation
Power supply	1 X 3V coin battery IEC-CR2032
Battery life	2-years with 7200-sec sampling rate
Dimensions	75.5 x 53 x 23.5 mm (2.95 x 2.16 x 0.9 in)
Weight	0.02 kg (0.044 lb)
Mechanical	
IP Rating	IP65
Agency Approvals & Certifications	CE - EMC Conforms to EN61326-1.

INCLUDED & REPLACEMENT PARTS

RS232 Cable
Download Suite CD
Instruction Manual

Amprobe® Test Tools
website: www.Amprobe.com
email: info@amprobe.com
Everett, WA 98203
Tel: 877-AMPROBE

Amprobe® Test Tools Europe
Amprobe Test Tools Europe
Beha-Amprobe GmbH
In den Engematten 14
79286 Glottental, Germany
Tel.: +49 (0) 7684 8009 - 0

©2008 Amprobe Test Tools. All rights reserved.
5/2008 3358073 Rev A