

FEATURES & BENEFITS



R-22id Refrigerant Identifier

Feature	Benefit
<ul style="list-style-type: none"> Stable non-dispersive infrared (IR) sensor 	Proven technology that does not rely on pressure or temperature measurements
<ul style="list-style-type: none"> Simple to understand LED driven status indicators 	Simple user-friendly operation with intuitive LED prompts reduces training time and cost
<ul style="list-style-type: none"> Ergonomically designed case with integral stand, magnetic mounting, and rubber over-molding 	Provides durability, robustness, and hands-free operation
<ul style="list-style-type: none"> 9 VDC operation for maximum portability and easy replacement 	Use in difficult locations without the need for AC power
<ul style="list-style-type: none"> Optional AC power adapter 	Affords continuous operation when AC power is readily available
<ul style="list-style-type: none"> Automatic calibration with onboard electric pump 	Provides consistent calibration before every test
<ul style="list-style-type: none"> Single push button operation 	Easy to use and efficient operation
<ul style="list-style-type: none"> Solid and blinking LED lights 	Solid lights indicate the unit is processing while blinking lights require user input
<ul style="list-style-type: none"> Oil resistant metal filter with simple, low cost replacement 	Significantly reduces oil contamination from overcharged systems
<ul style="list-style-type: none"> Low cost and high performance 	Economically use on every service truck with minimal expense
<ul style="list-style-type: none"> 95% pure R22 pass/ fail criteria 	Ensures that only R22 is recovered into the recovery tank to avoid costly contaminated refrigerant charges

25 June 2010




205 Westwood Ave
 Long Branch, NJ 07740
 1-877-742-TEST (8378)
 Fax: (732) 222-7088
 salesteam@Tequipment.NET