


BenQ MS513

Digital Projector



| | | |
|------------------------------------|---|--|
| Display Technology | DLP® by Texas Instruments® | |
| Native Resolution | SVGA (800 x 600) | |
| Resolution Supported | VGA (640 x 480) to UXGA (1600 x 1200) | |
| Brightness | 2700 ANSI Lumens | |
| Contrast Ratio | 10,000:1 (Full on / Full off) | |
| Image Size | 30" to 300" | |
| Throw Ratio | 1.97 to 2.17 (50" @ 2 meter) | |
| Zoom Ratio | Manual Zoom, 1.10:1 | |
| Projection Offset | 120% ±5% | |
| Keystone correction | 1D, vertical +/- 40 degrees | |
| Lens | F = 2.51 ~ 2.69, f = 21.95 ~ 24.18 mm | |
| Lamp Life* | 190W, 4500 / 6000 / 6500 hours (Normal / Economic / SmartEco mode) | |
| Lamp Warranty | 12 months or 2,000 cumulative hours whichever comes first | |
| Operational Noise | 29 / 27 dB (Normal / Economic mode) | |
| Displayable Colours | Full 1.07 billion color palette | |
| Aspect Ratio | 4:3 Native, 5 aspect ratio selectable | |
| Horizontal Frequency | 31 ~ 90 kHz | |
| Vertical Scan Rate | 50 ~ 120 Hz | |
| Interface | Computer in (D-sub 15pin) x 2 (shared with Component) Monitor out (D-sub 15pin) x 1 HDMI v1.3 x 1 Composite Video in (RCA) x 1 S-Video in (Mini DIN 4pin) x 1 | Audio in (Mini Jack) x 1 Audio out (Mini Jack) x 1 Speaker 2W x 1 USB (Type B) x 1 (Download & Page up/down) RS232 (DB-9pin) x 1 |
| Compatibility | Video Compatibility NTSC / PAL / SECAM HDTV Compatibility 480i / 480p / 576i / 576p / 720p / 1080i / 1080p 3D Compatibility PC: 120Hz Frame Sequential 3D for resolutions up to WXGA PC: 60Hz Top-bottom 3D for resolutions up to SXGA+ Video: 60Hz Frame Sequential 3D for resolutions up to 480i | |
| Dimensions (HxWxD) | 124 x 302 x 232.7 mm | |
| Weight | Net weight: 2.5 kg. Gross weight: 3.5 kg. | |
| Auto Switching Power Supply | 100 to 240 VAC, 50/60 Hz | |
| Power consumption | Normal mode: 245W, Standby < 1W SmartEco mode: 120W (will vary depending on the projected content) | |
| On Screen Display Languages | Arabic / Bulgarian / Croatian / Czech / Danish / Dutch / English / Finnish / French / German / Greek / Hindi / Hungarian / Indonesian / Italian / Japanese / Korean / Norwegian / Polish / Portuguese / Romanian / Russian / Simplified Chinese / Spanish / Swedish / Thai / Traditional Chinese / Turkish (28 Languages) | |
| Application Modes | Dynamic / sRGB / Presentation / Cinema / User 1 / User 2 | |
| Functions | SmartEco BrilliantColor™ Closed Captioning 3D Color Management Digital Zoom (x2) HDTV Compatible Windows 7 Certified High Altitude Mode | Instant Restart Quick Auto Search Wall Color Correction Freeze + blank Auto Off Security Password Security Bar + K-locker slot Presentation Timer |
| Accessories Included | Quick Start Guide Manual CD Remote Control w/battery | VGA Cable Power Cord |
| Accessories Optional | Presentation Plus RS232 Cable 3D Glasses | Spare Lamp Kit Ceiling mount Soft Carry Case |

* Lamp life results will vary depending on environmental conditions and usage.

All specifications are subject to change without notice. Available models (specs inc.) may vary from different regions.