
BenQ MW516

Digital Projector



















Display Technology	DLP® by Texas Instruments®	
Native Resolution	WXGA (1280 x 800)	
Resolution Supported	VGA (640 x 480) to UXGA (1600 x 1200)	
Brightness	2800 ANSI Lumens	
Contrast Ratio	10,000:1 (Full on / Full off)	
Image Size	30" to 300"	
Throw Ratio	I.46 to I.60 (62" @ 2 meter)	
Zoom Ratio	Manual Zoom, 1.20:1	
Projection Offset	120% ±5%	
Keystone correction	ID, vertical +/- 40 degrees	
Lens	F = 2.55 ~ 3.06, f = 21 ~ 25.6 mm	
Lamp Life*	190W, 4500 / 6000 / 6500 hours (Normal / Economic / SmartEco mode)	
Lamp Warranty	12 months or 2,000 cumulative hours whichever comes first	
Operational Noise	29 / 27 dB (Normal / Economic mode)	
Displayable Colours	Full 1.07 billion color palette	
Aspect Ratio	16:10 Native, 5 aspect ratio selectable	
Horizontal Frequency	31 ~ 90 kHz	
Vertical Scan Rate	50 ~ 120 Hz	
Interface	Computer in (D-sub 15pin) x 2	Audio in (Mini Jack) x I
	(shared with Component)	Audio out (Mini Jack) x I
	Monitor out (D-sub 15pin) x I	Speaker 2W x I
	HDMI vI.3 xI	USB (Type B) x I (Download & Page up/down)
	Composite Video in (RCA) x I	RS232 (DB-9pin) x I
	S-Video in (Mini DIN 4pin) x I	
Compatibility	Video Compatibility NTSC / PAL / SECAM	
	HDTV Compatibility 480i / 480p / 576i / 576p / 720p / 1080i / 1080p	
	PC: 120Hz Frame Sequential 3D for resolutions up to WXGA	
	3D Compatibility PC: 60Hz Top-bottom 3D for resolutions up to SXGA+	
	Video: 60Hz Frame Sequential 3D for resolutions up to 480i	
Dimensions (HxWxD)	124 x 302 x 232.7 mm	
Weight	Net weight: 2.5 kg. Gross weight: 3.5 kg.	
Auto Switching Power Supply	100 to 240 VAC, 50/60 Hz	
- table to the table to table to the table to	Normal mode: 245W, Standby < 1W SmartEco mode: 120W (will vary depending on the projected content)	
Power consumption		
On Screen Display Languages	Arabic / Bulgarian / Croatian / Czech / Danish / Dutch / English / Finnish / French / German / Greek /	
	Hindi / Hungarian / Indonesian / Italian / Japanese / Korean / Norwegian / Polish / Portuguese / Romanian	
	/ Russian / Simplified Chinese / Spanish / Swedish / Thai / Traditional Chinese / Turkish (28 Languages)	
Application Modes	Dynamic / sRGB / Presentation / Cir	nema / User I / User 2
Functions	SmartEco	Instant Restart
	BrilliantColor™	Quick Auto Search
	Closed Captioning	Wall Color Correction
	3D Color Management	Freeze + blank
	Digital Zoom (x2)	Auto Off
	HDTV Compatible	Security Password
	Windows 7 Certified	
		Security Bar + K-locker slot Presentation Timer
	High Altitude Mode	
Accessories Included	Quick Start Guide	VGA Cable
	Manual CD	Power Cord
	Remote Control w/battery	
Accessories Optional	Presentation Plus	Spare Lamp Kit
	RS232 Cable	Ceiling mount
	3D Glasses	Soft Carry Case

st Lamp life results will vary depending on environmental conditions and usage.

All specifications are subject to change without notice. Available models (specs inc.) may vary from different regions.





