BenQ MW712 Digital Projector





















Display Tochnology	DI P [®] hu Tavaa Instrumente [®]	
Display Technology	DLP® by Texas Instruments®	
Native Resolution	WXGA (1280 x 800)	
Resolution Supported	VGA (640 x 480) to UXGA (1600 x 1200)	
Brightness	3200 ANSI Lumens	
Contrast Ratio	10,000:1 (Full on / Full off)	
Image Size	35" to 300"	
Throw Ratio	1.46 to 1.60 (62" @ 2 meter)	
Zoom Ratio	Manual Zoom, 1.20:1	
Projection Offset	120% ±5%	
Keystone correction	I D, vertical +/- 40 degrees	
Lens	F = 2.55 ~ 3.06, f = 21 ~ 25.6 mm	
Lamp Life*	230W, 3500 / 5000 / 6500 hours (Normal / Economic / SmartEco mode)	
Lamp Warranty	12 months or 2,000 cumulative hours whichever comes first	
Operational Noise	31 / 28 dB (Normal / Economic mode)	
Displayable Colours	Full 1.07 billion color palette	
Aspect Ratio	16:10 Native, 5 aspect ratio selectable	
Horizontal Frequency	31 ~ 90 kHz	
Vertical Scan Rate	50 ~ 120 Hz	
Interface	Computer in (D-sub 15pin) x 2	Audio L/R in (RCA) x I
	(shared with Component)	Audio out (Mini Jack) × I
	Monitor out (D-sub 15pin) x 1	Speaker 10W x 1
	HDMI vI.3 xI	USB (Type B) x I (Download & Page up/down)
	Composite Video in (RCA) x I	LAN (RJ45) ×1 (LAN Control)
	S-Video in (Mini DIN 4pin) x 1	RS232 (DB-9pin) x I
	Audio in (Mini Jack) x I	
Compatibility	Video Compatibility NTSC / PAL / SECAM	
	HDTV Compatibility 480i / 480p / 576i / 576p / 720p / 1080i / 1080p	
	PC: 120Hz Frame Sequential 3D for resolutions up to WXGA	
	3D Compatibility PC: 60Hz Top-bottom 3D for resolutions up to SXGA+	
	Video: 60Hz Frame Sequential 3D for resolutions up to 480i	
Dimensions (HxWxD)	124 x 302 x 232 mm	
Weight	Net weight: 2.7 kg. Gross weight: 3.9 kg.	
Auto Switching Power Supply	100 to 240 VAC, 50/60 Hz	
	Normal mode: 285W, Standby < IW	
Power consumption	SmartEco mode: 140W (will vary depending on the projected content)	
	Arabic / Bulgarian / Croatian / Czech / Danish / Dutch / English / Finnish / French / German / Greek /	
On Screen Display Languages	Hindi / Hungarian / Indonesian / Italian / Japanese / Korean / Norwegian / Polish / Portuguese / Romanian /	
		/ Thai / Traditional Chinese / Turkish (28 Languages)
Application Modes	Dynamic / sRGB / Presentation / Cinema / User	l/llsor 2
Application Flodes		
	SmartEco	Instant Restart
	BrilliantColor™	Quick Auto Search
	Closed Captioning	Wall Color Correction
Functions	3D Color Management	Freeze + blank
	Digital Zoom (x2)	Auto Off
	HDTV Compatible	Security Password
	Windows 7 Certified	Security Bar + K-locker slot
	High Altitude Mode	Presentation Timer
Accessories Included	Quick Start Guide	VGA Cable
	Manual CD	Power Cord
	Remote Control w/battery	
Accessories Optional	Presentation Plus	Spare Lamp Kit
Accessories Optional	RS232 Cable	Ceiling mount
Accessories Optional	RS232 Cable 3D Glasses	Ceiling mount Soft Carry Case

All specifications are subject to change without notice. Available models (specs inc.) may vary from different regions.



вепо