



BenQ MX710 Projector

SPECIFICATIONS

HIGHLIGHTS

- USB reader and Plug-n-Play display
- Capable of displaying over LAN
- Filter-free design
- Crestron RoomView compatible
- 2700/3200 ANSI Lumens

Projection System	DLP® technology by Texas Instruments®
Native Resolution	XGA (1024 x 768)
Brightness	2700/3200 ANSI lumens
Contrast Ratio	5000:1 (Full on/Full off)
Keystone	Auto Keystone Vertical ± 40 Degree; Manual Vertical ± 40 Degree
Aspect Ratio	4:3 Native (5 selectable aspect ratio)
Color	Full 16.7 million color palette
Lens	F=2.59~2.87
Zoom Ratio	Manual Zoom, 1.3:1
Image Size (Diagonal)	32" to 300"
Throw Ratio	1.5 to 1.95(65"@2M)
Lamp	210W, 4000/5000 hrs ; 230W 3500/5000hrs (Normal/Economic mode)
Computer Compatibility	VGA(640 x 480) to UXGA (1600x1200)
HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility	NTSC, PAL, SECAM
Horizontal Frequency	31-99 kHz
Vertical Scan Rate	48-120 Hz
PC Input Terminals	Analog RGB: D-sub 15 pin x 2; LAN Networking: RJ-45 x1 (LAN Display); USB connector: Type A x 1 (USB thumb drive); USB Type mini B x 1 (USB display)
A/V Input Terminals	HDMI V1.3 x 1; S-Video: Mini Din 4 pin x 1; Composite Video: RCA x 1
Audio Input Terminals	Audio L/R : RCA x 1; Stereo Mini Jack x 1
PC Output Terminals	D-sub 15 pin x 1; Variable Audio Out : Stereo Mini Jack x 1; 12 V Trigger x 1
Audio Input Terminals	10W x 1
Control Terminal	Serial Connector : RS232 x 1; RJ45 x 1; USB mini Type B x 1(Page up/down) shared
Dimensions(W x H x D)	290mm x 102.97mm x 236.1mm
Weight	5.8 lbs (<2.65kg)
Power Supply	100 to 240 VAC, 50/60 Hz
Power Consumption	300W/ 320W, Standby < 1W
Audible Noise	31/27 dB; 33/28dB (Normal/Economic mode)
On-Screen DisplayLanguages	Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hungarian/ Indonesian/ Italian/ Japanese/ Kroean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (26 Languages)
Functions	BrilliantColor™; VIDITM; 3D Color Management; Crestron LAN Control; Closed Captioning; Digital Zoom (x2); Variable Audio Out; Quick Cooling; Quick Auto Search; Blank; Panel Key Lock; Auto Off; Security Password; HDTV Compatible; High Altitude Mode; "Q?" Hot Key for FAQ; 3D Ready; Freeze
Accessories (Standard)	Quick Start Guide; Manual CD; Remote control w/battery; VGA(D-sub) cable; Power cord; Soft carry case
Accessories (Optional)	Presentation Plus; RS232 Cable; Spare Lamp Kit



TOP



FRONT



BACK

Touchboards

205 Westwood Ave, Long Branch, NJ 07740
 Phone: 866-94 BOARDS (26273) / (732)-222-1511
 Fax: (732)-222-7088 | E-mail: sales@touchboards.com

Newline