Specifications

Model MP65E

Technology .79" 3LCD

Brightness 4500 Lumens (standard) 3800 (economy mode)

 $\begin{tabular}{ll} Native Resolution & 1024 x 768 (XGA) \\ Supported Resolution & 1600 x 1200 (UXGA) \\ \end{tabular}$

Colors 16.7 Million
Brightness Uniformity 85%

Projection Methods Desktop front/rear; Ceiling front/rear

Contrast Ratio 500::

Aspect Ratio Native 4:3; Compatible 16:9

Image Size 40" to 300" Projection Distance 4' to 30'

Lens Manual Zoom and Focus

Keystone Correction Vertical +/- 30 degrees Manual and Auto

Horizontal Scan Rate 35~107kHz Vertical Scan Rate 50~120Hz

Audio Output 1 x 8W mono speaker

Lamp 275W

Lamp Life 2000/3000 (standard/economy)

Remote Control Full Function IR remote with laser pointer

Noise Level 33dB standard 30dB economy mode

Power Supply AC Input 100–240V, Auto 50/60Hz

Power Consumption 430W

<5W in Standby mode

Computer Compatibility UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized; VESA

Standards; PC and Macintosh Compatible

Video Compatibility EDTV (480p), HDTV (720p, 1080i), NTSC/NTSC 4.43, PAL

B/G/H/I/M/N 60, SECAM

Connectivity Component (RCA x3) DVI-I, VGA-in, Composite Video, S-Video,

RCA Stereo Audio-In (x2), Mini-Jack Audio-In (x2), VGA-Out,

Mini-Jack Audio-Out

Service and Network Control RS232X, RJ45, USB mouse Control

Weight 16.5 lbs

Dimensions (W x H x D) 18.9" x 6.1" x 14.4" (480 x 155 x 365 mm)

Operating Temperature N/A

Standard Accessories AC power cord, VGA cable, USB cable Remote Control with

batteries, User manual (cd)

Optional Accessories Replacement remote control. Harsh Enviroment Filter

Component Video cable, DVI-D cable, Ceiling Mount,

S-Video Cable

LENS INFORMATION

Standard Lens 1.5-1.8 standard lens

Zoom Ratio 1.2

F= 1.7-1.9 f= 24~28.8

Outstanding Technical Support 24/7/365

And, of course, all **BOXLIGHT** products all come with free lifetime technical support. Speak with a hands-on, in-house, ISF Certified® technician ready to service your projector should the need arise.

© 2010 BOXLIGHT, Inc. Specifications subject to change without notice. Helps meet ADA Section 508 compliance BOXLIGHT NE 151 Highway 300, Suite A PO Box 2609 Belfair, WA 98528



Key Features

Five auto features (Auto Search, Auto Sync, Auto Ceiling, Auto

Keystone and Auto Filter Alert)


4500 Lumens

Robust input panel


Optional harsh enviroment filter

RJ45 Network ready

Side changing lamp and filter



Throw Distance (ft)



Diagonal Image Size (inches)

