

# Pro4500DP

Shine Some Serious Light

With a whopping 5000-lumen maximum capacity, this projector is ideal for big-impact presentations in large venues, even when the space is fully lit. For truly gigantic illumination and enhanced dramatic effect, stack several together and combine horizontal and vertical displays.



# Pro4500DP

## Specifications



### BRIGHTNESS

5000 Lumens Dual Lamp (Stand)  
 3000 Lumens Dual Lamp (Eco)  
 2500 Lumens Single Lamp (Stand)  
 2000 Lumens Single Lamp (Eco)

### RESOLUTION

1024 x768 XGA  
 1280x1024 SXGA (Supported)

### DISPLAY TYPE

Texas Instruments  
 0.7" x 1, 12° DDR

### CONTRAST RATIO

2000 :1

### ASPECT RATIO

4:3 Native  
 16:9 Compatible

### THROW RATIO

1.8 ~ 2.1 (x screen width)

### PROJECTION LENS

Powered Zoom / Focus  
 +/-50% Vertical  
 +/-15% Horizontal

### ZOOM RATIO

1.22:1

### DIAGONAL IMAGE SIZE

30" - 300"

### THROW DISTANCE

3.2" - 32.8"

### KEYSTONE

+/- 40° Vertical  
 +/-40° Horizontal

### LAMP

250 watt OSRAM E21.8

### LAMP LIFE

2000 Standard  
 3000 Eco

### INPUTS

DVI-D (HDCP) w/ 3.5 mm Audio  
 5-BNC (RGB,HV) w/ 3.5 mm Audio  
 Composite w/ RCA R/L Audio  
 RCA YPbPr w/ RCA R/L Audio  
 S-Video w/ RCA R/L Audio  
 HDMI

VGA (YPbPr) w/ 3.5 mm Audio

### OUTPUTS

VGA (YPbPr) w/ 3.5 mm Audio

### PROJECTOR CONTROLS

USB  
 RJ45 (LAN Control)  
 RS232 (9-Pin)  
 Wired Remote

### COMPATIBILITY

VGA,SVGA,XGA,SXGA, UXGA, Mac  
**EDTV / SDTV / HDTV**  
 480i/p,576i/p,720p,1080i  
 1080p (5-BNC Only)

### FCC CERTIFICATION

FCC-A, UL, TUV-CB, c-UL, CB, CE, CCC

### VIDEO COMPATIBILITY

NTSC / NTSC 4.43 / PAL B/G/H/I/M/N 60 /  
 SECAM

### AUDIO

3w x 2 Stereo Speakers

### DECIBEL RATING

35dB (standard) / 33dB (eco)

### H-REFRESH RATE

15-94 kHz

### V-REFRESH RATE

50-85 kHz

### POWER SUPPLY

AC 110 ~ 240 Volts  
 (auto ranging)

### POWER CONSUMPTION

650W (standard)  
 520W (eco)

### DIMENSIONS (WxDxH)

16.2" x 18.5" x 7.6" Inches

### WEIGHT

33 Lbs

### WARRANTY

3 year parts & labor / 90 day lamp

### Special features of the Pro4500DP include:

- Built in RJ-45 Lan connectivity,
- Intelligent dual lamp system
- (2) 3 Watt stereo speakers,
- power lens shift H/V,
- Email notification,
- 10 lens options,
- two fan speeds

