CEILING MOUNTS **RPMA[™] □** ELITE[®] PROJECTOR MOUNT





FEATURES

MICROZONE[™] ADJUSTMENTS PATENT-PENDING

This feature makes projector registration fast and precise (including flush-mount installations).

CENTRIS® TECHNOLOGY PATENT-PENDING

Enables effortless fingertip positioning. Selfadjusts to support different projector weights.

CABLE MANAGEMENT

SPECIFICATIONS

* Dimensions don't include interface bracket

±3°

±20°

360°

Black

2.75" x 6.5" x 5.5"

(69 x 165 x 140 mm)

Black, Silver, White

Pitch Adjustment

Point ±20°

50 lbs (22.7 kg)

Roll

Pitch

Yaw

Dimensions*

Color, Custom

Color, Universal

Weight Capacity

4.5

(HxWxD)

TECHNICAL DRAWINGS

5.5"

(140 mm) (114 mm

2.72" (69 mm)

Route cables through top of mount without additional accessories.

Q-LOCK[™] QUICK RELEASE LEVER

Provides quick connect/disconnect of the projector for service and enhanced security with an integrated key and lock system.

WHAT YOU NEED TO KNOW

ABOUT RPMA ELITE

- New universal interface with faster installation, and lamp and filter access •
- Keyed locking options (A/B/C/D) •
- Compatible with a wide array of accessories •
- Ships fully-assembled with everything you need for installation in one box
- Available in custom (black) or universal (black, silver, white)



RECOMMENDED ACCESSORIES



CMS EXTENSION COLUMNS

LSB101 Lateral Shift Accessory

For a complete list of projector mount accessories see page 18.



1-1/2" DIA NPT ۷ o 5.5' (140 mm) 1.0" -> 5.24" (133 mm) (25 mm)

6.5″

(165 mm)



Roll Adjustment Point ±3°





