

HT-3000

FAST • SAFE • RELIABLE



DIELECTRIC WITHSTAND (HIPOT) AC/DC PRODUCTION LINE TESTER

Features

- AC Output to 2000 volts; delivers up to 20mA, and DC output to 2800 volts; delivers up to 5mA.
- Logic controlled, one button test. LED's indicate test progress. Upon failure, buzzer sounds and testing is terminated.
- Output voltage, leakage current limit, voltage ramp-up time and test duration are controlled from the rear panel.
- Ground continuity test is defeatable for testing of two wire products.
- Two high voltage output connections; NEMA 5-15R receptacle and a high voltage test jack.
- Automatic voltage rampdown circuit eliminates residual voltage.
- Operation instructions provided on the rear panel.
- Performs to UL, CE, IEC, CSA, TUV safety agency requirements for production line testing.
- Ergonomically designed for safety, speed and efficiency.
- Calibration resistor mounted on rear panel.
- One year calibration cycle.
- Economical, durable and compact.
- Test leads included.
- **TEST-LINK** Compatible
- 30 day trial - 1 year warranty



HT-3000



ELECTRICAL

Output:	0-2000 Volts AC and 0-2800 Volts DC Pigtail and Receptacle adapters available for most configurations. Consult factory.
Leakage Current:	0-20 mA AC; 0-5 mA DC
Pass/Fail Criteria:	
Continuity:	3 ohm $\pm$ 5%* (defeatable)
Leakage Current:	Pass/Fail point user adjustable.
Dielectric Breakdown:	Separate high frequency detection circuit for breakdown spike detection.
Test Time:	User adjustable 1-60 sec.
Voltage Ramp-Up Time:	User adjustable .5-5 sec.
Voltage Ramp-Down Time:	Factory set 1 sec. approx.
Pass/Fail Repeatability:	$\pm$ 3%
Duty Cycle:	100%
Meter Accuracy:	$\pm$ 3% Full Scale
Test Adjustments:	Rear Panel: Ramp Time Test Time Leakage Limit Voltage Adjust
	Tamper-proof operation available by removing adjustment shafts.

ENVIRONMENTAL

Operating Temperature:	15-40°C
Relative Humidity Range:	0-90% non-condensing

GENERAL

Input Power Requirements:	Model HT-3000: 114-127 volts, 50/60 Hz Model HT-3000L: 98-120 volts, 50/60 Hz
Weight:	10.5 lbs.
Dimensions:	9.250 (W) x 4.250 (H) x 10.000 (L) in.

SAFETY

Transformer Output:	<500 VA
Visual Indication Of Voltage Output:	Provided by front panel meter, directly connected to high voltage output.
Failure Indication:	Audible, provided by internal buzzer Visual, provided by red LED's on front panel Test automatically terminated on failure.
Continuity Test:	Provided; 3 ohm pass/fail point. May be defeated for testing of products with two wire power supply cords.
Leakage Test:	Provided; 5mA AC/1 mA DC factory set pass/fail point, user adjustable. 120 Kohm calibration resistor provided on rear panel.
Operation Instructions:	Provided on rear panel.

1 Bethany Rd. Suite 58 Bldg 4, Hazlet, NJ 07730

Phone: 1-877-742-8378 Fax: (732) 335-1548

E-mail: evan@tequipment.net

Visit Us At: www.tequipment.net