





Safety and Accuracy - The Perfect Combo



The Dranetz-BMI series of DranTech digital meters and data loggers come with the patented automatic blocking safety (ABS) connector jacks* and IP 52 to even IP-65 water resistant protection* to prevent accidentally damaging the meter or injuring yourself while making 600V CAT IV and 1000V CAT III voltage* and current measurements. Safety plus exemplary technology with the highest resolution of handheld multimeters on the market, 60,000 counts* or more (1,200,000), autoranging current measurements from 10nA to 10A*, extra large display characters with analog bar graphs on a large light-blue illuminated display of the 23 or more functions.

These are the perfect tools for measuring power systems for balancing loads, energy efficiency measurement, electronic circuit analysis, insulation resistance testing, electrical system verification, and equipment tests, even with highly distorted signals such as adjustable speed drives. The high performance, precision measuring instruments are found in electrical contractors tool boxes, R&D labs, industrial applications, universities, hospitals, government authorities, testing stations, manufacturing and Quality Assurance departments

With the help of DranWIN software, momentary or stored measurement data acquired with DranTech multimeters can be read out, visualized, analyzed, stored and documented, and the measuring functions and ranges which are available for the position to which the function selector switch is currently set can be remotely controlled.

^{*} Refer to specification sheet on reverse side which ratings are appropriate for each model

- **PRO/XTRA** CAT III 1000V, CAT IV 600V DMMs with standard measurements (TRMS AC/DC for V and I, ohms, freq, diode, temperature, min/max, capacitance)
- **Drantech ISO** Insulation tester (range 5k ohms-3.1G ohms) as well as TRMS multimeter and data logger.
- PL10 Voltage disturbance recorder, data logger and power meter.
- **ULTRA** High precision multimeter (0.004% and 1.2M counts) and milli-ohm measurements, plus data logger.
- **OUTDOOR** All of the standard DMM measurements when you need to operate in environment needing IP-65 (NEMA 4) water & dust resistance
- **PMIT** All-in-One Milliohm Resistance Meter, DMM, Data Logger, and Insulation Resistance Tester (outer skins-wick test, lightning protection)

| Features | PRO | XTRA | PL10 | ULTRA | OUTDOOR | PMIT | ISO |
|--|--------------|--------------|--------------|---------|--------------|--------|--------------|
| Basic dc volts accuracy % | 0.05 | 0.05 | 0.025 | 0.004 | 0.05 | 0.25 | 0.15 |
| Bandwidth | 50kHz | 100kHz | 100kHz | 100kHz | 100kHz | 1kHz | 10kHz |
| Maximum Display Counts* (+/-) | 60,000 | 60,000 | 310,000 | 1,200k | 12,000 | 31,000 | 31,000 |
| True RMS Volts ac/dc | 1000V | 1000V | 600V | 600V | 1000V | 600V | 1000V |
| True RMS Current ac/dc* | 10A (16A) | 10A (16A) | 10A (16A) | 100mA | 10A (16A) | | 10A (16A) |
| CAT II/III 600V * | | | CAT III | CAT III | | CAT II | CAT III |
| CAT II/III 1000V * | CAT III | CAT III | | | CAT III | | CAT II |
| CAT IV 600V * | CAT IV | CAT IV | | | CAT IV | | |
| Ohms / Audible Continuity | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| dBs | | Yes | Yes | | | | |
| Frequency | 100kHz | 1MHz | 300kHz | 100kHz | 100kHz | 3kHz | 300kHz |
| Precision MilliOhm and Kelvin Connection, 4-wire measurement | | | | Yes | | Yes | |
| Capacitance / Diode Test | Yes | Yes | Yes | | Yes | diode | Yes |
| Temperature | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Offset Rel/Ref / Min/Max/Hold | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Auto/Manual Ranging | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Analog Bar Graph | Yes | Yes | | | Yes | Yes | Yes |
| Triple Display | | | Yes | Yes | | | |
| Backlight | Yes | Yes | | | Yes | Yes | Yes |
| Insulation Test @ 50/100/250/500 | | | | | | Yes | Yes+1kV |
| Power and Energy Measurements | | | Yes | | | | |
| Voltage Disturbance Recording | | | Yes | | | | |
| Memory for Datalogging | | 540kB | 128kB | 128kB | 540kB | 32kB | 540kB |
| IR-Interface for USB Data Xfer | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Low Pass filter 1KHz | Yes | Yes | | | Yes | Yes | Yes |
| AC Power Supply Adapter | | Yes | Yes | Yes | Yes | Yes | Yes |
| Housing Protection | IP52 | IP52 | IP50 | IP50 | IP65 | IP65 | IP54 |
| Change Fuse & Bat w/o opening | Yes | Yes | | | Yes | Yes | Yes |
| ABS Patented Connections* | Yes | Yes | Yes | | Yes | | Yes |

Specifications are subject to change without notice. Refer to specific product's User Guides for detailed specifications.



www.dranetz-bmi.com

1.800.372.6832

sales@dranetz-bmi.com tel 732.287.3680 : fax 732.248.1834 1000 New Durham Road, Edison, New Jersey 08818 USA © 2008 Dranetz-BMI. All rights reserved. Printed in United States.











