

Digital Viscotesters

Battery operated viscosity meter, one button operation, choice of High or Low range model

Features:

- Direct readings on large digital display
- Measuring range:
 - Model 345055 Low range - 1.5 to 330mPa-s (1.5 to 330cP)
 - Model 345060 High range - 0.3 to 4000dPa-s (30 to 400,000cP)
- Accurate to 5% of reading
- One button turns the motor on and selects the rotor
- Use as handheld or with optional lab stand with base
- Sample temperature to 300°F (150°C)
- Fast, accurate determination of fluid viscosity
- Popular for fluids with viscosity ranging from castor oil or honey to tar
- Ideal for adhesives, paint, oils and fats, inks, pulp, rubber, foods, petroleum products, and cosmetics
- Dimensions: 7x6.7x3.5" (177.8x165.1x88.9mm)
Weight: 1.72lbs (0.78kg)
- Complete with three interchangeable rotors, one sample cup, case, stand, and four AA batteries



Complete Kit includes rotors, cups, holder for lab stand, and case.



Optional lab stand with base clip.

Ordering Information:

- 345055**Digital Viscotester (Low range 1.5 to 330cP)
- 345060**Digital Viscotester (High range 30 to 400,000cP)
- 345104**Lab Stand with base clamp

EXTECH INSTRUMENTS CORPORATION
285 Bear Hill Road, Waltham, MA 02451-1064, U.S.A.
Phone: 781-890-7440 • FAX 781-890-7864

ISO 9001:2000 CERTIFIED

Make mine an Extech!
www.extech.com



10/03 - R1