

Appliance Tester/Power Analyzer

Compact, battery operated device for analyzing AC power loads

With PC interface plus datalogging

Features:

- Four simultaneous displays of Watts. Power Factor or VA, Voltage or Hz, Amps
- True RMS Voltage & Current measurements of sine, square, triangular and distorted wave forms with a crest factor < 5
- Max, Data Hold and Overload Protection
- Battery or AC adaptor provides line isolation
- Plug device to be tested directly into the Power Analyzer
- Sampling (update) rate is 2.5 times/second
- Windows® 95/98/NT/2000/XP/ME software allows user to download stored data or save data directly, and to create an ASCII file. Computations include phase angle, apparent and reactive power, consumption and cost, and power factor correction
- · Complete with Windows compatible software, cable, 8 x AA batteries, power cord, 117 VAC adaptor and case

Applications:

- Measure and Audit power consumption of single phase devices
- Evaluate load performance under varying line conditions
- · Demonstrate effectiveness of power conservation efforts
- Characterize device AC power requirements

Model 380803 Datalogger

 Built-in Datalogger stores up to 1,012 readings (Single record storage or continuous datalogging)

Model 380801

Used for data acquisition when connected to a PC

Ordering Information:

| True RMS Single Phase Power Analyzer |
|--------------------------------------|
| 380801 with NIST Certificate |
| True RMS Power Analyzer Datalogger |
| 380803 with NIST Certificate |
| Portable Thermal Printer |
| Thermal Paper for PR20 (6 pack) |
| RS-232 to USB Adaptor |
| |





Optional Thermal Printer (PR20) prints text or graphics with fixed intervals or continuous



Software included to download and store data to a PC



Built-into heavy duty carrying case.

| Specifications: | Range | Resolution | Basic Accuracy (%rdg) | Input Signal Range |
|-------------------|--|-------------|----------------------------|---------------------|
| Watt | 200/2000W | 0.1/1W | $\pm (0.9\% + 4d)@50/60Hz$ | 300V, 20A, 40-400Hz |
| Power Factor | 0.5 to 1.0 | 0.001 | (Based on W, V, A) | 250V, 20A, 50/60Hz |
| Voltage | 200.0/750V | 0.1/1V | ±(0.5%) | 1000VDC, 750VAC |
| Current | 2/20A via terminals | | ±(0.5%) | (Fuse Protection) |
| | 2/15A via sockets | | | |
| Frequency | 40Hz to 20kHz | 1Hz to 10Hz | ±(0.5%) | |
| Dimensions/Weight | 13.9 x 11.8 x 3.9" (352 x 300 x 100mm) / 3.6 lbs. (1.6 kg) | | | |







