

1000A True RMS Power Clamp Meter

Measurements include Power (kW), Current (μA), Insulation Resistance (MΩ) and Temperature

Features:

- Large dual LCD display (9999 count)
- Measures True Power (kW), Apparent Power (kVA) and Phase Angle with Lead/Lag indicator
- AC+DC μA current with 10nA resolution for flame rod tests
- Max/Min recording with elapsed time indication
- Auto Detect AC/DC Voltage measurements with simultaneous frequency display
- Capacitance to 7000μF with 0.001μF resolution
- High Resistance tests to 100MΩ
- Type K, °C/°F switchable, temperature to 1000°F
- Diode and Continuity tests
- Auto power off with disable feature
- 1.6" (40mm) clamp jaw opening
- Complete with test leads, Type K probe, carrying case and 9V battery

Applications:

- AC Power evaluation
- Motor/Generator installation and repair
- HVAC flame rod tests
- Capture max/min temperature or current values
- Category III rating for industrial measurements

CE CAT III-600V

Function	Max Range / Resolution	Basic Accuracy
True Power (W):	600kW / 10W	±5%+ 20d
Apparent Power (kVA):	600kVA / 10kVA	±2%+ 20d
Phase Angle (φ):	-45 to +40° / 0.1°	±3°
AC Current: (Trms):	1000A / 10mA	±2%+ 20d
μA Current (AC+DC) (Irrms):	1000μA / 10nA	±1%+ 20d
AC/DC Voltage: (Trms):	600V / 0.1mV	±1%+ 20d
Resistance (Ω):	1000kΩ / 0.1Ω	±1%+ 10d
Resistance (MΩ):	100MΩ / 1kΩ	±5%+ 10d
Capacitance:	7000μF / 1nF	±1.5%+ 5d
Frequency:	40Hz to 1kHz / 0.1Hz	±0.5%+ 2d
Temperature (Type K):	-58 to 1000°F / 0.1°F -50 to 900°C / 0.1°C	±1%+ 2°F ±1%+ 1°C
Frequency:	40Hz to 1kHz / 0.1Hz	±1%+ 2d
Dimensions:	9 x 3 x 1.6" (228 x 76 x 39mm)	
Weight:	16.4oz (465g)	



Ordering Information:

380975True RMS Power Clamp Meter
 380975-NISTTrue RMS Power Clamp Meter with NIST Certificate
 480172AC Line Splitter

EXTECH INSTRUMENTS CORPORATION
 285 Bear Hill Road, Waltham, MA 02451-1064, U.S.A.
 Phone: 781-890-7440 • FAX 781-890-7864

ISO 9001:2000 CERTIFIED

Make mine an Extech!
www.extech.com



08/03 - R1