

Product DATASHEET

Clamp-On Ground Resistance Tester

Enables non-contact measurements of ground conductors without need for auxiliary ground spikes

Features:

- Ground resistance measurements down to 0.03Ω with 0.02Ω maximum resolution
- True RMS AC Leakage current range of 0.2mA to 15A with 0.001mA maximum resolution
- · Clearly marked Rotary Switch operation
- Simplifies ground resistance measurements on multiple point ground systems
- 0.9" Jaw Size for Large Ground Rods
- Electrical Noise Detection feature prevents inaccurate readings
- · Verification Resistors Confirm accuracy of Meter
- Data Hold and Continuity Beeper
- · Automatic Self Calibration when powered on
- 9999 Count High Contrast LCD Display
- Complete with 9V battery, Resistance check plate and carrying case

CAT III-300V,

Specifications	Range	Resolution	Accuracy (%rdg)
Ground Resistance:	0.03 to 9.99Ω	0.02Ω	$\pm (1.5\% + 0.1\Omega)$
	10.0 to 99.9Ω	0.1Ω	$\pm (2.0\% + 0.3\Omega)$
	100.0 to 199.9Ω	0.4Ω	$\pm (3.0\% + 1.0\Omega)$ typical
	200.0 to 399.9Ω	2Ω	$\pm (5.0\% + 5\Omega)$ typical
	400.0 to 599.9Ω	5Ω	$\pm (10\% + 10\Omega)$ typical
	600.0 to 999.9Ω	10Ω	Not specified
	1000 to 1500Ω	30Ω	Not specified
AC Leakage Current (Trms):	0.200 to 0.999mA	0.001mA	±(2.5% + 0.05mA)
	1.000 to 9.99mA	0.01mA	±(2.5% + 0.05mA)
	10.00 to 99.9mA	0.1mA	±(2.0% + 0.3mA)
	100.0 to 750.0mA	0.1mA	±(2.5% + 3mA)
	0.20 to 15.00A	0.01A	±(2.0% + 0.05A)
Continuity:	Beep if less than 40Ω (approximately)		
Dimensions:	10.2 x 4.4 x 1.9" (258 x 110 x 47mm)		
Weight:	24.7oz (700g)		·

EXTECH GROUND RESISTANCE HOLD Ω

Applications:

- Verify resistance of cellular and communcation tower ground grids
- Check utility transmission systems and grounding rods
- Maintenance on electric transportation systems
- Ideal for grounding systems in sub-stations, factories and office buildings

Ordering Information:

