

## CH Product DATASHEET

## **Moisture Meter**

Monitor moisture in wood and other building materials

## **Features:**

- Dual Measurement Scale LCD Display with Bargraph
- Measures Wood Moisture from 6 to 44%
- Measures Building Material Moisture from 0.2 to 2.0%
- Use on wall board, sheet rock, cardboard, plaster, concrete, and mortar
- Self-contained, pocket sized meter with belt clip
- Replaceable measurement electrode pins
- Impact proof housing
- Battery operated for on-the-go measurements
- · Auto Power OFF conserves battery energy
- · Built-in battery check and functionality test
- Complete with protective cap and three (3) CR-2032 button batteries



Convenient pocket size meter



## $\epsilon$

Specifications:	
Display	Dual measurement scale LCD with bargraph metering
Wood Moisture Range	6 to 44%
Basic Accuracy	±1%
Other Building Materials	0.2 to 2.0%
Basic Accuracy	±0.05%
Measurement principle	Electrical resistance
Electrode length	0.3" (8mm)
Electrode pins	Integrated, replaceable
Auto Power Off	After approx. 15 minutes
Operating Temperature	32 to 104°F (0 to 40°C)
Operating Humidity	85% Relative Humidity maximum
Power supply	Three CR-2032 button cells
Dimensions	5.1 x 1.6 x 1.0" (130 x 40 x 25mm)
Weight	3.5 oz (100g)

**Ordering Information:** 

MO200.....Moisture Meter

