

Fiber Optic Power Meter

Link certification and reporting tool

Features:

- 65dB Dynamic range
- Capable of both single mode and multimode operation
- 1mm Germanium photodetector with 2.5mm universal adaptor (ST, SC and FC)
- Simple four button operation
- Large easy to read backlit LCD display
- Stores up to 100 data points
- Serial port and Reporter™ data management and reporting software
- Software based Loss Wizard™
- >100hr battery life
- Basic 0.15dB accuracy with 0.01dB resolution
- Complete with NIST Certificate, Windows® 95/98/NT/2000/ME/XP compatible software, serial cable, 9V battery, and protective rubber holster



Specifications:

Range (dBm):	+5 to -60
Resolution:	0.01dB
Accuracy:	±0.15dB
Wavelengths:	850nm, 1310nm, 1550nm
Multimode:	Yes
Single Mode:	Yes
Data Storage:	100
Software:	Yes
Battery Life:	9V battery/>100 hours
Dimensions:	4.9x2.8x1.3" (125x70x33mm)
Weight:	10oz (283g)

Ordering Information:

PM200Fiber Optic Power Meter

EXTECH INSTRUMENTS CORPORATION
285 Bear Hill Road, Waltham, MA 02451-1064, U.S.A.
Phone: 781-890-7440 • FAX 781-890-7864

ISO 9001:2000 CERTIFIED

"Make mine an Extech!"™
www.extech.com



09/30