

Dual Display Model SC52 Clamp-on Meter

The SC52 is like having two meters in one. Designed for the HVAC/R technician, you can display AAC while also displaying any of the meter's other main functions. In addition to common electrical parameters, the SC52 measures **microamps DC** (μ ADC). The NCV (non-contact voltage) easily and safely detects the presence of AC voltage down to 24VAC.

Features	
Versatile	<ul style="list-style-type: none"> ■ Volts, μADC, ohms, continuity, and amps. ■ Display AMPS AC through clamp and VOLTS through leads at the same time. ■ Extremely compact and portable.
Safe	<ul style="list-style-type: none"> ■ NCV warns that there is a live AC voltage on the wire without actually touching it.
Easy to use	<ul style="list-style-type: none"> ■ Autoranging selects the best range for the best possible resolution.

Specifications			
Parameter	Ranges	Accuracy	Best Resolution
VAC	4, 40, 400 600	$\pm 1.2\%rdg + 5dgt$ s $\pm 1.5\%rdg + 5dgt$ s	1m
VDC	4, 40, 400, 600	$\pm 0.5\%rdg + 2dgt$ s	1m
AAC	40, 400	$\pm 2.0\%rdg + 6dgt$ s	0.01
μ ADC	400, 4000	$\pm 1.0\%rdg + 2dgt$ s	0.1
Ohms	400, 4k, 40k, 400k 4M 40M	$\pm 1.0\%rdg + 4dgt$ s $\pm 1.5\%rdg + 4dgt$ s $\pm 3.0\%rdg + 5dgt$ s	0.1
Continuity	BEEP < 25 Ω		



205 Westwood Ave
Long Branch, NJ 07740
1-877-742-TEST (8378)
Fax: (732) 222-7088
salesteam@Tequipment.NET



Model: SC52 H26-652

