



205 Westwood Ave
Long Branch, NJ 07740
1-877-742-TEST (8378)
Fax: (732) 222-7088
salesteam@Tequipment.NET

Supplement

Title: 700HTP-1 I.S. Supplement Issue: **2**
Part Number: 2811836 Issue Date: 2/10
Print Date: April 2007 Page Count: 1
Revision/Date: Rev.1, 11/08

This supplement contains information necessary to ensure the accuracy of the above Instruction Sheet.

Change #1

Under *Introduction*, replace the second bullet with the following:

- Hydraulic media: distilled water, mineral based hydraulic oil, or up to hydraulic oil 100 (30 W).

Under *Box Contents*, add the following bullet:

- 1/4 in. NPT male to 1/8 in. NPT male fitting

Under *Priming the Pump*, replace step 1 with the following:

1. Before making any connections to the pump, remove the filler cap (item ⑧) and fill the reservoir approximately 2/3 with either distilled water, mineral oil, or hydraulic oil and re-install the filler cap until finger-tight.

Delete step 4, and renumber accordingly.

Under *Features*, replace No. 5 with the following:

⑤	Hydraulic fluid reservoir	Holds 100 cc of hydraulic fluid: mineral based hydraulic oil, distilled water, or hydraulic oil.
---	---------------------------	--



205 Westwood Ave
Long Branch, NJ 07740
1-877-742-TEST (8378)
Fax: (732) 222-7088
salesteam@Tequipment.NET