

# True RMS AC/DC Clamp-on Multimeter LH2015

- 2,000A AC and DC Amps
- Large jaw capacity takes 50mm Ø or 2 x 30mm Ø cables
- Analysis of AC and DC current components
- Autoranging and Auto-zeroing
- Excellent accuracy, even for distorted or non-sinusoidal A
- Display-Hold and Max-Hold (surge) modes for convenience in use
- Conformance to IEC1010 and EMC standards



## High Accuracy

Advanced jaw design means that 15-series accuracy is little affected by external magnetic fields or off-centre conductor positioning. Utilisation of Hall effect technology ensures a broad flat frequency response resulting in optimum accuracy even when harmonics are present.

## True RMS measurement

By using True RMS measurement techniques the 15-series instruments avoid errors (up to 50%) which can occur when non-sinusoidal waveforms created by today's complex loads are measured using traditional average-reading techniques. True RMS measurements are available for AC, DC and AC+DC amperes.

## IEC 1010 and EMC Conformance

IEC 1010 safety features including a tactile barrier and special jaw design provide the user with confidence when making measurements in hazardous voltage areas.

Conformance to EMC standards ensures high reliability through reduced susceptibility to electromagnetic interference.

NON-INVASIVE CURRENT MEASUREMENT	
Ranges (auto-ranging)	400A, 2,000A
Measurement methods	AC True RMS, or DC only
Resolution	100mA (400A range) 1A (2,000A range)
Accuracy	± 1.3% of reading ± 3 digits > 10A (1)
Crest Factor	6 maximum for True RMS measurements
Maximum measurable load	2,000A DC or AC peak
Maximum overload	10,000 Amps



## Frequency Response

(Measurements and Analogue Output)

AC only True RMS V & A	15Hz to 1kHz (3,4)
DC True RMS A	DC + 15Hz to 1KHz (3,4)
DC V and A	DC only

## Display

Size and type	4000-count LCD 12mm / 0.5-inch characters
Status indication	Low Battery, Data Hold, Pk (MAX Hold), AC, DC, Diode Test, $\Omega$ , $\llcorner$ ) (Continuity)
Refresh rate	3 times per second

## Power Supply

Battery type	9 V Alkaline: MN1604, PP3 IEC 6LR61 or equivalent
Battery life	Typically 40 hours

## Mechanical Data:

Dimensions (H x W x D):	251 x 98 x 52 mm 9.88 x 3.86 x 2.05 inches
Weight:	500gm / 1.1 lbs
Jaw Capacity:	1 x 50 mm/ 2.0-inch $\varnothing$ cables or 2 x 30mm/ 1.2-inch $\varnothing$ cables
Jaw Opening	55mm/ 2.2 inches

## Environmental Data:

Operating Temperature:	0 °C to 50 °C (32 °F to 122 °F)
Temperature Coefficient (Current)	$\pm 0.1\%$ of reading per °C $\pm 0.06\%$ of reading per °F
Storage Temperature:	-20° to 60° (-4 °F to 140 °F)

## Safety:

All models comply with IEC1010-1, 600V working, Installation category III, Pollution degree 2.

## Maximum Safe Voltages:

Current measurement (bare conductors)	600V AC RMS or DC between uninsulated conductor & ground
Voltage measurement	600V AC RMS or DC between input terminals or between live terminal & local ground.

## LEM

LEM offers a comprehensive range of electrical test products to ensure the safe and efficient operation of electrical equipment and installations. Other products from the LEM group includes systems and analysers for power quality and power quality monitoring and transducers for current and voltage measurement. LEM provides complete measurement solutions in current, voltage and power quality.

## Notes:

1. All accuracies stated at 23°C  $\pm$  1°C (73.4  $\pm$  1.8°F)
2. Analogue output is form plug-in adaptor with standard BNC output socket
3. At stated accuracy, extend to 5kHz for 3dB point
4. True RMS measurements taken over 100ms

[www.fluke.com/](http://www.fluke.com/) [www.fluke.co.uk](http://www.fluke.co.uk)

Printed in EU  
Technical modifications reserved  
Pub-ID 10969-eng

**Fluke Corporation**  
P.O. Box 9090  
Everett, WA 98206  
U.S.A.  
Tel.: (800) 443-5853  
Fax: (425) 446-5116

**Fluke Europe B.V.**  
P.O. Box 1186  
5602 BD Eindhoven  
The Netherlands  
Tel.: 31 (0)40 2675 200  
Fax: 31 (0)40 2675 222

In June 2005  
**Fluke Corporation**  
acquired LEM Instruments.



**FLUKE**®